

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other2. NAME OF OPERATOR  
Union Texas Petroleum Corporation3. ADDRESS OF OPERATOR  
P.O. Box 1290, Farmington, New Mexico 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1830' FSL; 1760' FEL

AT TOP PROD. INTERVAL: Same as above

AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Perforations ☐

## SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐RECEIVED  
DEC 23 1983BUREAU OF LAND MANAGEMENT  
FARMINGTON RESOURCE AREA5. LEASE  
SF 078430

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Newsom A

9. WELL NO.

20

10. FIELD OR WILDCAT NAME

Wildcat Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 4, T26N-R8W NMPM

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6800' GR

(NOTE) Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

The Greenhorn/Gallup perforations are 7022,20,16,10,05,01; 6998,91,87,82,78,68,58,46,36,25,11 for a total of 17 shots.

The Lower Gallup perforations are 6755,46,36,21,13; 6698,86,78,72,67,60,55,46,44,36,30,25,20,06; 6592 for a total of 20 shots.

The Middle Gallup perforations are 6528,23,14,03; 6496,89,81,76,54,47,38,32,25,19,09,04; 6398,94,91,84,81 for a total of 21 shots.

The Upper Gallup perforations are 6332,28,24,14,10,04,00; 6296,92,84,75,60,58,50,48,37,34,30,26,22 for a total of 20 shots.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED J A Edmister TITLE Engineering Analyst DATE December 16, 1983  
J A. Edmister

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side.

NMOCC