

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR

AAA OPERATING COMPANY, INC.

3. ADDRESS OF OPERATOR Suite 3545

First International Bldg. Dallas, Texas 75270

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1500'FNL, 1680'FWL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other)

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

DEC 19 1983

U.S. GEOLOGICAL SURVEY
FARMINGTON RESOURCE AREA

5. LEASE
NM-05791

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal "M"

9. WELL NO.
1-A

10. FIELD OR WILDCAT NAME
Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 3-T27N-R8W
N.M.P.M.

12. COUNTY OR PARISH San Juan 13. STATE N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5835'GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/15/83 T.D. 4850'. Ran 115 joints 4-1/2", 10.50 Lb., J-55 casing (4878.30') set at 4850' with:

First Stage: 660 cu. ft. 50-50 Pozmix with 6-1/4 lbs. Gilsonite and 6 lbs. salt per sack. Calculated top of cement 3300'.

Second Stage: 1576 cu. ft. 65-35 Pozmix (12% Gel) with 6-1/4 lbs. Gilsonite per sack, followed by 59 cu.ft. Class "B" Neat Cement. Top of cement as per Temperature Survey - 425'.
Stage Collar - 3317'

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

FOR: AAA OPERATING COMPANY, INC.

18. I hereby certify that the foregoing is true and correct.

SIGNED EWELL N. WALSH TITLE Walsh Engr. & Prod. Corp. DATE 12/20/83

Ewell N. Walsh, PE President

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DEC 23 1983

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

BY SMW

U.S. GEOLOGICAL SURVEY
FARMINGTON RESOURCE AREA
DIV. 3 - NMOC