UNITED STATES

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM-05791
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas 🗔	Federal "M"
well Well W other	9. WELL NO. 3
2. NAME OF OPERATOR	10. FIELD OR WILDCAT NAME
R. C. WYNN 3. ADDRESS OF OPERATOR Suite 3545 75270	
First International Bldg. Dallas, Texas	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 3-T27N-R8W
below)	N.M.P.M.
AT SURFACE: 1700'FSL, 1800'FWL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same	San Juan N.M.
AT TOTAL DEPTH: Same	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 5855 G.L.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	<u></u>
REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MILITIPLE COMPLETE	- D
FRACTURE TREAT	VE
SHOOT OR ACIDIZE	•
REPAIR WELL DE REPAIR OF ALTER CASING DE REPAIR WILL DE REPAIR WELL DE REPAIR WEL	1984OTE: Report results of multiple completion or zone MANAGE AREA ON Form 9-330.)
PULL OR ALTER CASING U	NAGE AREA
MULTIPLE COMPLETE U MAIN CHANGE ZONES MAN MAN ANI	OURCE
ABANDON*	ESS
(other) BUREMING	
SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	
2/18/84 T.D. 3325'. Ran 80 joints 4-1/2 (3308') set at 3320.60' with:	", 9.50 lb., K-55 casing
1041 cu. ft. 65/35 Pozmix with 6 sack, followed by 264 cu. ft. 50	/50 Pozmix (2% Gel) with
6-1/4 lbs. Gilsonite and 6 lbs.	salt per sack. Cement
circulated to surface.	CEIVEM
circulated to surface. MAR 05 1984	
OIL COM 5.	
Subsurface Safety Valve: Manu. and Type	Set @Ft.
FOR: R. C. WYNN 18 I hereby certify the database for explained in the forest formalist in the forest	IST. 3

Malsh Engr. & ALSH THE Prod. Corp. President DRIGNALESIONED BY EWELL N. WALSH DATE (This space for Federal or State office use) ACCEPTED FOR RECORD

NMOCC

MAR 0 2 1984

*See Instructions on Reverse Side

FARMINGTON REGOGNOE AREA

RY