

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
R. C. WYNN
3. ADDRESS OF OPERATOR Suite 3545
First International Bldg. Dallas, Texas 75270
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2380'FNL, 1380'FEL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐ ☒
FRACTURE TREAT ☐ ☐
SHOOT OR ACIDIZE ☐ ☐
REPAIR WELL ☐ ☐
PULL OR ALTER CASING ☐ ☐
MULTIPLE COMPLETE ☐ ☐
CHANGE ZONES ☐ ☐
ABANDON* ☐ ☐
(other) ☐ ☐

5. LEASE
SF-078476
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Federal "R"
9. WELL NO.
3
10. FIELD OR WILDCAT NAME
Largo Chacra
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 15-T27N-R8W
N.M.P.M.
12. COUNTY OR PARISH
San Juan
13. STATE
N.M.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5938'GL

RECEIVED
MAR 01 1984

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

NOTE: Base results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2/18/84 Spud Well
2/19/84 T.D. 278'. Ran 6 joints 8-5/8", 24.0 lb., K-40 casing (263.20') set at 277.20' with 325 cu. ft. Class "B" cement with 3% Calcium Chloride and 1/4 lb. Flocele per sack. Cement circulated. Pressure test with 500 psig. Test ok.
2/24/84 T.D. 3385'. Ran 82 joints 4-1/2", 9.50 lb., K-55 casing (3366.05') set at 3378.55' with:
1096 cu. ft. 65/35 (12% Gel) Pozmix with 6-1/4 lbs. Gilsonite per sack followed by 330 cu. ft. 50/50 Pozmix (2% Gel) with 6-1/4 lbs. Gilsonite and 6 lbs. salt per sack. Cement circulated to surface.

Subsurface Safety Valve: Manu. and Type _____ to surface _____ Ft.

FOR: R. C. WYNN
18. I hereby certify that the foregoing is true and correct
ORIGINAL SIGNED BY Walsh Engr. & Prod.
SIGNED Ewell N. Walsh, P.E. President TITLE Corporation DATE 2/29/84

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____ ACCEPTED FOR RECORD

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAR 05 1984

NR000

*See Instructions on Reverse Side

MAR 02 1984

FARMINGTON RESOURCE AREA

RV San

