

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Floyd Operating Company

3. Address and Telephone No.

711 Louisiana, Suite 1740, Houston, Texas 77002

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1741' FSL and 1098' FWL Sec 33, T26N, Rg12W

5. Lease Designation and Serial No.  
N00-C-14-20-7464

6. If Indian, Allottee or Tribe Name  
Navajo Alloted

7. If Unit or CA, Agreement Designation

L

8. Well Name and No.

Navajo "LB" #2

9. API Well No.

30-045-25987

10. Field and Pool, or Exploratory Area

Bisti Farmington

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Plug by spotting following plugs:

1. 100' of Class 'B' + 6% gel plug 518' - 618' across Bisti Farmington @ 588'.
2. Perforate 50' below surface casing set @-85. Pump Class B + 6% gel down 2 7/8" and circulate to surface.
3. Cut casing off 3' below ground level and install Regulation Dry Hole Marker.

A 40 sec/qt. viscosity, 8.34 lb/gal. mud will be used to spot all plugs.

14. I hereby certify that the foregoing is true and correct

Signed

Title Manager of Production

Date 6/2/93

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

APPROVED  
AS AMENDED

JUN 28 1993

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side  
NIMOC

DISTRICT MANAGER