

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well

GAS

2. Name of Operator

MERIDIAN OIL

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1820'FSL, 810'FWL, Sec.21, T-26-N, R-9-W, NMPM

5. Lease Number

SF-078060A

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

Huerfano Unit

8. Well Name & Number

Huerfano Unit #136E

9. API Well No.

30-045-26241

10. Field and Pool

Basin Dakota

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

3-22-95 MIRU. ND WH. NU BOP. PT BOP. TOO H w/tbg. TIH w/4 1/2 cmt retainer, set @ 6385'. SDON.

3-23-95 TIH w/4 1/2" cmt retainer, set @ 6387'. PT tbg to 1000 psi, OK. Establish injection. Plug #1: pump 30 sx Class "B" cmt below cmt retainer & 8 sx Class "B" cmt above cmt retainer, TOC @ 6335'. TOO H to 6261'. Load hole w/wtr. PT csg to 500 psi, OK. Circ hole clean. TOO H to 5510'. Plug #2: pump 12 sx Class "B" cmt @ 5362-5510'. TOO H to 3648'. Establish injection. Plug #3: pump 12 sx Class "B" cmt @ 3548-3650'. TOO H to 2052'. Establish injection. Plug #4: pump 78 sx Class "B" cmt @ 998-2052'. TOO H. TIH to 283'. Establish circ. Plug #5: pump 30 sx Class "B" cmt @ 0-284'. Circ 1 bbl cmt to surface. ND BOP. Cut off WH. Install dry hole marker w/10 sx cmt. RD. Well plugged and abandoned 3-23-95.

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct.

Signed *Regina Starnes* Title Regulatory Affairs Date 3/31/95

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

Date

CONDITION OF APPROVAL, if any:

APPROVED

APR 05 1995

DISTRICT MANAGER

NMOCD