

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CON.

OIL CON. DIV.

OIL CONSERVATION DIVISION

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

	NAME RESE	RVOIR OR	POOL		TYPE PROD	METHOD PROI	MEDIUM PROD
JPR COMP	BLANCO MESAVERDE 95		5728	GAS	FLOW	TBG	
LWR	BASIN DAKO	TA	9	5727	GAS	FLOW	TBG
	l	PR	E-FLOW	SHUT-IN P	RESSURE DA	ATA	
	Hour/Date	Shut-In	Lengt	h of Time	Shut-In	SI Press.	PSIG Stabilzed
PR COMP	08/13/90		72 Hours			32D	
LWR	08/13/90			72 Hours		421	/
	1		- F	LOW TEST	DATE NO.1		
Comme	nced at (ho	our,date)*				Zone Pr	oducing (Upr/Lw
TIME LAPSED To the control of the co		3	E PRESSURE Upper Lower		Prod Temp.	REMARKS	
0	8/13/90	Day	1 ,	270	409		Both Zones SI
0	8/14/90	Day	2	270	420		Both Zones SI
0	8/15/90	Day	3	B2C	421		Both Zones SI
08/16/90 E		Day	4	320	NS!		lowed lower
08/17/90 Da		Day	5	336/409 373			1 1
	8/18/90		6	343/411	373		11 / 11
	ction rate						
							_ Grav GOR _
Gas:			MFCPD	:Tested t	neu (Orifi	ce or Meter)	:METER
			MID-TES	ST SHUT-I	N PRESSURE	DATA	
UPR COMP		e SI Lei	ngth of	Time SI	SI Press	. PSIG Sta	bilized (yes/

JOHN THANK MIN

commenced at (hour, da		r·	FLOW TEST N			
TIME (hour, date)	LAPSED TIME SINCE ##	PRESSURE		Zone producing (Upp	r or Lowert:	
(100, 000)		Upper Completion	Lower Completion	PROD. ZONE TEMP.	REMARKS	
•	,			•		
	•			*** · · · · · · · · · · · · · · · · · ·		
				i		
				:		
_		ĺ				
duction rate du	ring test	_	·	<u>'</u>		
-				•		
	BOPD	based on	Bbls. in	House	Grav GOR	
:		• • • • •		110tils	GOR	
		——— MCFPI	D: Tested thru (C	rifice or Meter):	Grav GOR	
narks:				. •		
					·-	
						
		•			f my knowledge.	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

Date

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the otder authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disrurbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Original Stated by bitters

DEPUTY OIL & GAS INSPECTOR

New Mexico Oil Conservation Division

By

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).