

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

SF 077806

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Huerfano Unit

8. FARM OR LEASE NAME

Huerfano Unit

9. WELL NO.

119E

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 15, T-26-N, R-10-W
NMPM

12. COUNTY OR PARISH 13. STATE

San Juan

NM

14. PERMIT NO.

FEB 10 1986

15. ELEVATIONS (Show whether DF, ET, GR, etc.)

6616' GL

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data
BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Running Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-3-86

TD 6835'. Ran 170 jts. 4 1/2", 10.5 & 11.6#, J-55 production casing 6823' set @ 6835'. Float collar set @ 6818'. Stage tools @ 4948' and 2327'. Cemented first stage with 182 sks. Class "B" 65/35 Poz mix, 6% gel, 2% calcium chloride (295 cu.ft.) followed by 100 sks class B, 50/50 POZ mix, 2% gel, 2% calcium chloride, 1/4# fine tuf-plug/sk (124 cu ft). 2nd stage with 275 sks. Class "B" 65/35 Poz mix, 6% gel, 2% calcium chloride (445 cu.ft.), 3rd stage with 661 sks. Class "B", 65/35 Poz mix with 6% gel and 2% calcium chloride (1071 cu.ft.). WOC 18 hours. Circulated to surface.

RECEIVED

FEB 20 1986

OIL CON. D.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drilling Clerk

DATE ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

FEB 18 1986

CONDITIONS OF APPROVAL, IF ANY:

FARMINGTON RESOURCE AREA

BY

*See Instructions on Reverse Side