

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1040' FSL, 1640' FWL, Sec. 15, T-26-N, R-10-W, NMPM

5. Lease Number
SF-077806

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

Huerfano Unit

8. Well Name & Number
Huerfano U #119E

9. API Well No.
30-045-26673

10. Field and Pool
Basin Dakota

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☒ Abandonment

☐ Change of Plans

☐ Recompletion

☐ New Construction

☒ Subsequent Report

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Final Abandonment

☐ Altering Casing

☐ Conversion to Injection

☐ Other -

13. Describe Proposed or Completed Operations

9-2-97 MIRU. SDON.

9-3-97 TIH to 4527'. TOOH. Load tbg w/40 bbl wtr. Pressure up to 1500 psi. TOOH w/tbg. TIH w/gauge ring to 3537'. TOOH. SDON.

9-4-97 TIH w/4 1/2" CIBP, set @ 6530'. TOOH. TIH, load hole w/wtr & circ hole clean. Plug #1: pump 13 sx Class "B" neat cmt @ 6360-6530'. TOOH. PT csg to 500 psi failed. Plug #2: pump 12 sx Class "B" neat cmt @ 5515-5676'. WOC. TIH, tag TOC @ 5515'. Load hole & circ clean. PT csg to 500 psi, failed. Circ hole clean. Plug #3: pump 14 sx Class "B" neat cmt @ 3586-3767'. WOC. SDON.

9-5-97 TIH, tag TOC @ 3630'. (Joe Ruyblid, BLM on location). Circ hole clean. PT csg to 500 psi, failed. Plug #4: pump 27 sx Class "B" neat cmt @ 1847-2200'. Plug #5: pump 25 sx Class "B" neat cmt w/2% calcium chloride @ 1302-1847'. Load hole w/wtr. PT csg to 500 psi, OK. Plug #6: Pump 24 sx Class "B" neat cmt. TOOH. TIH, tag TOC @ 982'. Circ hole clean. PT csg to 350 psi/5 min, OK. TOOH. TIH, perf sqz holes @ 290'. Establish circ down csg & out bradenhead. Plug #7: pump 32 sx Class "B" neat cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. ND BOP. Cut off WH. Fill csg w/8 sx Class "B" neat cmt. SD for weekend.

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed

Title Regulatory Administrator Date 10/1/97

(This space for Federal or State Office use)

APPROVED BY /s/ Duane W. Spencer Title

Date

OCT 16 1997

CONDITION OF APPROVAL, if any:

NMOC

9-8-97 Install dry hole marker w/10 sx Class "B" neat cmt. RD. Rig released. Well plugged and abandoned 9-8-97.