Form Approved.

## Dec. 1973 Budget Bureau No. 42-R1424 UNITED STATES 5. LEASE DEPARTMENT OF THE INTERIOR SF-078433 **GEOLOGICAL SURVEY** 6. IF INDIAN, ALLOTTEE OR TRIBE NAME - 7. UNIT AGREEMENT NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) 8. FARM OR LEASE NAME Newsom 1. oil gas XX well other well 9. WELL NO. 2. NAME OF OPERATOR 4-RROMO CORPORATION 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR Ballard Pictured Cliffs P.O. Box 1785, Farmington, N.M. 87499 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 18-T26N-R8W 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 N.M.P.M. below.) 1620'FNL, 1470'FEL AT SURFACE: 12. COUNTY OR PARISH 13. STATE N . M . San Juan AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same 14. API NO. 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6234 GR REPORT. OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT RECEIVED SHOOT OR ACIDIZE REPAIR WELL (NOTE: Report results of multiple completion or zone PULL OR ALTER CASING change on Form 9-330.) SEP 04 1986 MULTIPLE COMPLETE CHANGE ZONES ABANDON\* BUREAU OF LAND MANAGEMENT FARMINGTON RESOURCE AREA (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* 8/27/86 Spud Well 8/27/86 T.D. 170'. Ran 4 joints 8-5/8", 24.0 1b., K-55 casing (156.62') set at 170.62' with 184.08 cu. ft. Class "B" cement with 2% Calcium Chloride per sack. Cement circulated. Pressure test with 500 psig. Test ok. 8/29/86 T.D.2150'. Ran 52 joints 4-1/2", 10.50 lb., K-55 casing 2123.49' set at 2134.24' with 500 gallons mud flush followed by 411 cu. ft. 65/35 Pozmix, 12% Gel and 6-1/4 lbs. Gilsonite per sack followed by 198 cu. ft. 50/50 Pozmix, 2% Gel and 6-1/4 lbs. Gilsonite per sack. Acetic Acid spoted on plug. Insert Float 2093 Coment Circulated? Subsurface Safety Valve: Manu. and Type \_ FOR: ROMO CORPORATION 18. I hereby certify that the foregoing is true and correct Walsh Engineering ORIGINAL SIGNED BYTLE & Production Corp. DATE SIGNED EWELL N. WALSH (This space for Federal or State office use) SEP 1.8 1986 APPROVED BY TITLE DATE CONDITIONS OF APPROVAL, IF ANY: FARMINGTON NEGOVINOE AKEA