

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐		2. NAME OF OPERATOR El Paso Natural Gas Company		3. ADDRESS OF OPERATOR P.O. Box 4289, Farmington, NM 87499		4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements) At surface 1450'N, 1190'E At top prod. interval reported below At total depth		5. LEASE DESIGNATION AND SERIAL NO. SE-078135		6. IF INDIAN, ALLOTTEE OR TRIBE NAME		7. UNIT AGREEMENT NAME Huerfanito Unit		8. IF INDIAN, ALLOTTEE OR TRIBE NAME Huerfanito Unit		9. WELL NO. 150		10. FIELD AND POOL, OR WILDCAT Basin Fruitland Coal		11. SEC. T. R. M. OR BLOCK AND SURVEY OR AREA Sec. 01, T26N, R09W		12. COUNTY OR PARISH San Juan		13. STATE NM									
15. DATE SPUDDED 12-14-88		16. DATE T.D. REACHED 12-30-88		17. DATE COMPL. (Ready to prod.) 12-30-88		18. ELEVATIONS (OF RKB, RT, GR, ETC.)* 6116' GL		19. ELEV. CASINGHEAD 6116'		20. TOTAL DEPTH, MD & TVD 1892'		21. PLUG. BACK T.D., MD & TVD N/A		22. IF MULTIPLE COMPL., HOW MANY*		23. INTERVALS DRILLED BY ROTARY TOOLS CABLE TOOLS Yes		24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 1717-1891' Fruitland Coal		25. WAS DIRECTIONAL SURVEY MADE No		26. TYPE ELECTRIC AND OTHER LOGS RUN None		27. WAS WELL CORRED No									
28. CASING RECORD (Report all strings set in well)																																	
CASING SIZE		WEIGHT, LB./FT.		DEPTH SET (MD)		HOLE SIZE		VENTING RECORD		AMOUNT PULLED																							
9 5/8"		32.3#		241'		12 1/4"		177 cf																									
7"		20#		1758'		8 3/4"		600 cf																									
29. LINER RECORD																																	
SIZE		TOP (MD)		BOTTOM (MD)		SACKS CEMENT*		SCREEN (MD)		30. TUBING RECORD																							
5 1/2"		1709'		1892'						SIZE		DEPTH SET (MD)		PACKER SET (MD)																			
5 1/2"		1709'		1892'						2 3/8"		1882'																					
31. PERFORATION RECORD (Interval, size and number)																																	
1717-1891' W/4 SPF Pre drilled liner.																																	
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.																																	
DEPTH INTERVAL (MD)												AMOUNT AND KIND OF MATERIAL USED																					
33.* PRODUCTION																																	
DATE FIRST PRODUCTION				PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing-capable of comm. HC; to be sold when connected										WELL STATUS (Producing or shut-in) SIWOPL																			
DATE OF TEST		HOURS TESTED		CHOKES SIZE		PROD'N. FOR TEST PERIOD		OIL—BSL.		GAS—MCF.		WATER—BSL.		GAS-OIL RATIO																			
FLOW. TUBING PRESS.		CASING PRESSURE		CALCULATED 24-HR'R RATE		OIL—BSL.		GAS—MCF.		WATER—BSL.		OIL GRAVITY-API (CORR.)																					
SI-360		SI-632																															
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be sold BHP @ 1890' 376 psig																		TEST WITNESSED BY															
35. LIST OF ATTACHMENTS None																																	
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records																																	
SIGNED <i>[Signature]</i>												TITLE Regulatory Affairs												DATE 2-1-89									

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	945'	1200'	ss. White cr-grn s.	Ojo Alamo Kirtland Fruitland	945' 1200' 1650'	
Kirtland	1200	1650	Gry sh interbedded w/tight gry fine-grn ss.			
Fruitland	1650'	1892'	Gry carb sh, scattered coals, coals and gry, tight, fine-grn ss.			