

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate.
Other instructions on reverse side.

Expires August 31, 1995
LEASE DESIGNATION AND SERIAL

SF-078461

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.

1. WELL ☐ GAS ☒ WELL ☒ OTHER ☐	2. UNIT AGREEMENT NAME
3. NAME OF OPERATOR Union Oil Co. of Calif.	4. FARM OR LEASE NAME Filan
5. ADDRESS OF OPERATOR P.O. Box 671 - Midland TX 79702	6. WELL NO. 9
7. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. (See also space 17 below) At surface 1475' FSL & 790' FWL	8. FIELD AND POOL OR WILDCAT Basin Fruitland Coa
9. PERMIT NO.	10. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 5, T. 2N, R. 2W
11. ELEVATIONS (Show whether OF, RT, GR, etc.) 6420' GR	12. COUNTY OR PARISH San Juan
	13. STATE NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data	
NOTICE OF ABANDONMENT TO: ☒ TEST WATER SHUT-OFF ☐ FRACTURE TREAT ☐ SHOOT OR ACIDIZE ☐ REPAIR WELL ☐ Other	SUBSEQUENT REPORT OF: ☐ WATER SHUT-OFF ☐ FRACTURE TREATMENT ☐ SHOOTING OR ACIDIZING ☐ Other
☐ PULL OR ALTER CASING ☐ ABANDONMENT ☐ Other	☐ REPAIRING WELL ☐ ALTERING CASING ☐ ABANDONMENT

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

5/15 363' RUN 8-5/8" CSG. 363' 1/4. SURF ROCK. 3/4" @ 363'. MUD: 8.6, 60. MI RU ARAPAHOE RIG #2 (SD) 12-1/4" SURF HOLE @ 9:30 PM 5-15-90. TO SURF HOLE TO 363' @ 2:45 AM 5-16-90. CIRC 1/2 HR, POOH. RUNNING 8-5/8" CSG, INCOMP.

5/16 1545' DRLG. 1182' 8-3/4. SD & SH. 3/4" @ 891', 3/4" @ 1390'. MUD: 8.4, 32, 11, 1/32, 9.0, 500. R&C 7 JTS + 1 PC (349') 8-5/8" 20# X-42 BRD NEW SMLS CSG @ 362', CMT'D W/350 SXS CLASS "B" W/2% CACL & 1/4# CELLOCEAL @ 15.6 PPG. DISPLACED W/21 BFW @ 5 BPM @ 150 PSI. CIP & JC @ 6:00 AM 5-16-90. CIRC 95 SXS CMT. WOC 4 HRS. WELD ON CSG HD. NU BOP'S. TSTD BLIND RAMS, 8-5/8" CSG TO 600 PSI FOR 30 MINS, OK. TIH TO TOC @ 325'. TSTD PIPE RAMS TO 600 PSI FOR 30 MINS, OK. TOTAL WOC 13-3/4 HRS. DRLD PLUG & CMT TO SHOE. DRLG NEW FORM @ 7:45 PM 5-16-90.

5-19: 2616' TD, MORT. CIRC 1-1/2 HRS MADE SHORT TRIP, CIRC 3/4 HR. POOH. RAN OPEN HOLE LOGS TO 1773' & STOPPED. RIH W/8IT TO 2616'. CIRC & COND MUD 1-3/4 HRS, POOH. RAN MRL-GR-SDL FRM 2615' LTD TO 362'. TIH, CIRC 1/2 HR. LDDP & DC'S. R&C 60 JTS + 1 PC (2603') 4-1/2" 11.60# J-55 LT&C BRD NEW SMLS CSG @ 2616' W/DV TOOL @ 2179'. CMT'D 1ST STG W/150 SXS CLASS "H" CMT W/.9% FLO-LOK, .18% THRIFTY LITE, 3% KCL, 3# HI-SEAL @ 15.9 PPG. DISPLACED CMT W/10 BFW & 31 BBLs MUD @ 5 BPM @ 475 PSI. BMPD PLUG W/1000 PSI. FLOAT HELD OK. DROPPED OPENING BOMB OPENED DV TOOL, CIRC 4 HRS. CIRC 59 SXS CMT TO SURF. CMT'D 2ND STG W/530 SXS OF PACESETTER LITE CMT W/.8% CF-1, 1/4# CELLOCEAL, 3# HI-SEAL @ 12.6 PPG F/B 50 SXS CLASS "B" CMT @ 15.6 PPG. DISPLACED CMT W/34 BFW @ 4-1/2 BPM @ 500 PSI. BMPD PLUG & CLOSED DV TOOL W/2000 PSI. CIP & JC @ 4:45 AM 5-19-90. CIRC 120 SXS CMT. SET SLIPS, CUT OFF 4-1/2" CSG. RIG REL @ 7:00 AM 5-19-90.

18. I hereby certify that the foregoing is true and correct

SIGNED Charlotte Beeson TITLE Drilling Clerk

DATE 5-21-90

This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE

NMOCD

ACCEPTED FOR RECORD

DATE

MAY 25 1990

FARMINGTON RESOURCE AREA

*See Instructions on Reverse Side

BY 222

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.