Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED Budget Bureau No. 1004-0135

Expires: March 31, 1993

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

| BUREAU OF LAND MANAGEMENT 91 JEN -8 ANI | 5. Lease Designation and Serial No. |
|---|---|
| SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals | 6. If Indian, Allottee or Tribe Name |
| SUBMIT IN TRIPLICATE | 7. If Unit or CA, Agreement Designation |
| i. Type of Well Oil X Gas Well Other | 8. Well Name and No. |
| 2. Name of Operator Giant Exploration & Production Company | North Bisti Coal 31 #1 9. API Well No. |
| 3. Address and Telephone No. P.O. Box 2810, Farmington, N.M. 87499 (505) 326-3325 | 10. Field and Pool, or Exploratory Area |
| 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 800' FSL, 800' FWL, Sec. 31, T26N, R12W | Basin Fruitland Coal 11. County or Parish, State |
| | San Juan, New Mexico |
| 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR | T, OR OTHER DATA |
| TYPE OF SUBMISSION TYPE OF ACTION | |
| Notice of Inter Abandonment Recompletion Plugging Back Casing Repair Altering Casing Altering Casing Prilling Progress | Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water |

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled out from under casing with 6-1/4" bit December 18, 1990. Drilled to TD of 1300'. Ran Compensated Density-Neutron logs with gamma ray. Log tops as follows: Fruitland - 1005', Basal Fruitland Coal - 1128', Pictured Cliffs -1178'. Ran 31 jtc. (1298.35') of 4-1/2", 9.5#, J-55, 8rd, ST&C casing. BakerLoked cement nosed guide shoe on bottom and insert flapper float on top of 1st jt. Ran centralizers on tops of 1st, 3rd, 5th, 7th, and 9th jts. Casing set at 1296.64', PBD at 1260.19'. Cemented casing as follows: Mixed and pumped 70 sks. (144.2 cu. ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk. cellophane flakes. Tailed in with 75 sks. (88.5 cu. ft.) of Class "B" cement containing 2% CaCl $_2$ and 1/4#/sk. cellophane flakes. Cement circulated to surface. Pressure tested casing to 3500 psi for 15 minutes. Test ok. Waiting on completion operations.

| 4. I hereby dertify that the foregoing is true and correct Signed President | JAN 7 1991 |
|--|--------------------------|
| (This space for Federal or State office use) | ACCEPTED FOR RECORD |
| Approved by Title Conditions of approval, if any: | FEB 0 5 1991 |
| | FARMINGTON RESOURCE AREA |