Form 3160-5 (June 1990)

1 Type of Well XX Oil Well

2. Name of Operator

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires: M...ch 31, 1993

5. Lease Designation and Serial No. NM 65382

SUNDRY NOTICES AND REPORTS ON WELL'S

Do not use this form for proposals to drill or to deepen of reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Giant Exploration & Production Company

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

South Bisti #32-G

8. Well Name and No.

9. API Well No.

3 Address and Telephone No.		30-045-28484
PO Box 2810, Farmington, New Mexico 87	499 (505) 326-3325	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		Bisti Lower Gallup
		11. County or Parish, State
2310' FNL, 2310' FEL, Sec. 32, T26N, R1	3W	
		San Juan, New Mexico
CHECK APPROPRIATE BOX(s) TO INDIC	ATE NATURE OF NOTICE, REPOR	T, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Int D & G & C & C	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report FEB1 1 1991	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandon Office CON. DIV.:	Altering Casing	Conversion to Injection
	XXOther <u>Drilling Progress</u>	Dispose Water
DIST. 3		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled,

Drilled out from under casing with 7-7/8" bit January 14, 1991. Drilled to TD of 5350'. Ran Induction Log with Gamma Ray and Compensated Density-Neutron logs with caliper. Log tops as follows: Basal Fruitland Coal - 1440', Pictured Cliffs - 1518', Lewis - 1609', Cliffhouse - 2253', Menefee - 2846', Pt. Lookout -3967', Mancos - 4111', Gallup - 5060'. Ran 123 jts. (5361.49') of 5-1/2", 15.5#, J-55, 8rd, LT&C casing. BakerLoked cement nosed guide shoe on bottom and differential fill float collar on top of 1st jt. Ran centralizers on middle of 1st jt. and the tops of the 3rd, 5th, 7th, 9th and 11th jts. Casing set at 5349.77', PBD at 5304.66'. Cemented casing as follows: Mixed and pumped 500 sks. (1945 cu. ft.) Class "B" cement containing 3% A-2 extender and 1/4#/sk. cellophane flakes. Tailed in with 200 sks. (236 cu. ft.) of Class "B" cement containing 2% CaCl2 and 1/4#/sk. cellophane flakes. Cement circulated to surface. Pressure tested casing to 3500 psi for 15 minutes. Test ok. Waiting on completion operations.

Signed Collins True and correct Signed Collins President	Date JAN 2 8 1991
(This space A FRENCH SILLE OF KUCHERA MYH	ACCEPTED FOR RECORD
Approved by Title Conditions of approval, if any:	FEB ^{Da} 7 1991
	FARMINGTON RESOURCE AREA

