Form	3160-5
(June	1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED					
Budget Bureau No. 1004-0135					
Expires: March 31, 1993					

5. Lease Designation and Serial No.

, ;	SĮ	7-07	8156		
6	·lf	Indian,	Allottee or	Tribe	Name

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals

7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well X Oil Well Gas Well 8. Well Name and No. 2. Name of Operator Salge Federal A#5 Dugan Production Corp. 9. API Well No. 3. Address and Telephone No. 30-045-28578 P.O. Box 420, Farmington, NM 87499 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Bisti Lower Gallup 1730' FSL & 595' FWL 11. County or Parish, State Sec. 33, T26N, R13W, NMPM SEP 2 3 1991 San Juan, NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Conversion to Injection Other Spud & casing Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in & rigged up Four Corners Drilling Company Rig #6. Spudded a 12-1/4" hole at 4:30 P.M. 9-9-91. Drilled to 222'. Ran 5 jts. 8-5/8" OD, 24#, 8 Rd, ST&C casing (T.E. 205') set @ 217' RKB. Cemented with 135 sx class "B" cement with 2% CaCl2 (total cement slurry = 159 cu.ft.). Good mud returns while cementing. Circulated 2 bbls cement to surface. P.O.B. @ 9:00 P.M. 9-9-91. Nippled up BOP. Pressure tested casing and B.O.P. 1000 psi for 30 minutes - held OK.

> ACCEPTED FOR RECORD SEP 10 1991

	RESOURCE AREA	
14. I hereby certify that the foregoing is true and correct		
Signed Tim I Prophe	TideGeologist BY	Dete 9-10-91
(This space for Federal or State price use)		
Approved by	Title	Date
Conditions of approva; if any.		