

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

FOR APPROVED
OMB NO. 1004-0137
Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

NM-36590

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. NET AGREEMENT NAME

8. FARM OR LEASE NAME, WELL NO.

Rick Wells #2

9. API WELL NO.

30-045-28754

10. FIELD AND POOL, OR WILDCAT

Basin Fruitland Coal

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 9, T26N, R13W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. ENVIR. ☐ Other

2. NAME OF OPERATOR

Giant Exploration & Production

3. ADDRESS AND TELEPHONE NO.

P.O. Box 2810; Farmington, NM 87499 (505) 326-3325

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface

790' FSL, 790' FWL, Sec. 9, T26N, R13W

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED

11-2-92

16. DATE T.D. REACHED

11-5-92

17. DATE COMPL. (Ready to prod.)

6-15-93

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

6306' GLE

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

1580'

21. PLUG BACK T.D., MD & TVD

1529'

22. IF MULTIPLE COMPL., HOW MANY*

N/A

23. INTERVALS DRILLED BY

→

ROTARY TOOLS

X

CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

1403' - 1421'

26. TYPE ELECTRIC AND OTHER LOGS RUN

Compensated Density - Neutron logs with caliper and gamma ray.

25. WAS DIRECTIONAL SURVEY MADE

Yes

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
7"	20#	128.70'	8-3/4"	See Exhibit "A"	
4-1/2"	9.5#	1575.71'	6-1/4"	See Exhibit "A"	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2-1/16"	1407'	

31. PERFORATION RECORD (Interval, size and number)

1403' - 1421' 0.40" 72 Holes

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
1403' - 1421'	Fraced with 5600# 40/70
	Brady Sand, 16,297# 12/20
	Brady Sand

33. PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)					WELL STATUS (Producing or shut-in)	
6/15/93		Flowing					Shut-in	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO	
6/15/93	24 Hours	1/4"	→	-0-	No flow	-0-	-0-	
FLOW, TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)		
-0-	173	→	-0-	No flow	-0-			

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold.

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records.

SIGNED

[Signature]

TITLE Vice President Operations

DATE

JUN 18 1993

*(See Instructions and Spaces for Additional Data on Reverse Side)

JUN 23 1993

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Fruitland	1256'					
Basal Fruitland	1403'					
Pictured Cliffs	1448'					

38.

GEOLOGIC MARKERS

RECEIVED
JUN 28 1993
OIL CON. DIV.
DIST. 3

CEMENT RECORD

Surface Casing - Mixed and pumped 60 sks. (70.8 cu.ft.) of Class "B" cement containing 2% CaCl_2 and 1/4#/sk. cellophane flakes. Cement circulated to surface.

Production Casing - Mixed and pumped 100 sks. (206.0 cu.ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk. cellophane flakes. Tailed in with 90 sks. (106.2 cu.ft.) of Class "B" cement containing 2% CaCl_2 and 1/4#/sk. cellophane flakes. Cement circulated to surface.

ment