Form 3160-5 UNITED STATES **PORM APPROVED** 5 BLM (June 1990) dget Buress No. 1004-0135 DEPARTMENT OF THE INTERIOR 1 File Expires: March 31, 1993 **BUREAU OF LAND MANAGEMENT** 5. Lease Designation and Serial No. SF-078156A SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE I. Type of Well Well X Gas Other 8. Well Name and No. 2. Name of Operator Cisco Com #91 Dugan Production Corp. 9. API Well No. J. Address and Telephone No. 30 045 28805 P.O. Box 420, Farmington, NM 87499 10. Field and Pool, or Exploratory Area (505) 325-1821 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Basin Fruitland Coal 11. County or Parish, State 790' FSL & 790' FWL (Unit M) San Juan, New Mexico Sec. 34, T26N, R13W 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Abandonment Change of Plans Recompletion **New Construction** Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Altering Casing Conversion to Injection Other T.D. 45" casing J Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 1420' reached on 11/18/92. Conditioned hole. Laid down drill pipe. Ran IES & CDL logs by Great Guns Logging. Rigged up and ran 34 jts. 4½" OD, 10.5#, 8 Rd, ST&C casing (T.E. 1426.73') set at 1419' G.L. Cemented with 100 sx 2% lodense followed by 60 sx class "B" (*note: all cement has ½# celloflake per sk). Total cement slurry = 265 cu.ft. Preceded cement with 25 bbls water. Circulated all water and trace of cement to surface. Bumped plug with 1000 psi - float held OK. P.O.B. at 5:15 P.M. 11-18-92.

14. I hereby certify that the foregoing is true and correct			
Signed from 1 faces	Tide	Vice-President	Dete 11/19/92
(This/space for Federal or Salte office use) Approved by Conditions of approval, if any:	Tide		Dete
			ACCEPTED FOR REPUBL
ide 18 U.S.C. Section 1001, makes it a crime for any perior representations as to any matter within its jurisdiction.	on knowingly and willfully	to make to any department or agency of the	ne United States any false, fictitious or fraudulent statem

*See Instruction on Reverse Side