

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
SG Interests I, Ltd. *Maralex*

3. Address and Telephone No.
P. O. Box 421, Blanco, NM 87412-0421

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
2350' FSWL & 1650' FWL
NE/SW Section 17, T26N, R11W

5. Lease Designation and Serial No.
SF079679

6. If Indian, Allottee or Tribe Name
-

7. If Unit or CA, Agreement Designation
-

8. Well Name and No.
Gallegos Federal 26-11-17#2

9. API Well No.

10. Field and Pool, or Exploratory Area
Basin Fruitland Coal

11. County or Parish, State
San Juan County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Well Shut-Off
☐ Conversion to Injection

Production Casing

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Production Casing: TD @ 1568' on 1-05-93

Hole Size: 6 1/4"

Casing: 36 Jts (1553.74') 4 1/2", 10.5#, J-55, ST&C, Casing set @ 1558', Guide Shoe @ 1557', Float Collar @ 1513', 10 Centralizers @ 1538', 1496', 1412', 1328', 1244', 1160', 1076', 992', 908', & 824'.

Cement: 105 sx Class B w/2% Meta-Silicate & 1/4 pps Celo-Flake (2.06 Yield/216 cu ft) + 75 sx Class B w/2% CaCl & 1/4 pps Celo-Flake (1.19 Yield/89 cu ft). No cement circ to surface. Top of cement will be determined upon completion when CBL is run.

Bump Plug w/1000 psi.

Plug Down @ 10:15 PM on 1-04-93.

14. I hereby certify that the foregoing is true and correct

Signed *Terrell A. Baze*

Title Agent

(915) 694-6107

Date 1/12/93

(This space for Federal or State office use)

Approved by
Conditions of approval, if any:

Title

Date

NMOC

JAN 26 1993