

CEMENT JOB DETAIL SHEET

P.O. BOX 302
FARMINGTON, NEW MEXICO 87499

CUSTOMER S&G Enterprises		DATE 11-6-01	FR. 700133411	SER. SUP. W. O	TYPE JOB PD 4
LEASE & WELL NAME - OCSG #2 W. Dist. 26-13-20		LOCATION Loc 20-726-R134		COUNTY Son Juan	
DRILLING CONTRACTOR RIG # Key #6		OPERATOR			

MATERIAL FURNISHED	TYPE OF PLUGS	LIST CSG HARDWARE	SQ MANI FOLD Y ☒	TOP OF EXCH FLUID	PHYSICAL SLURRY PROPERTIES					
					SLURRY WEIGHT PPG	SLURRY YIELD FT ³	WATER GPS	PUMP TIME HR: MIN	BD SLURRY	BD MIX WATER
70 SK Spot @ 18'				900	15.6	1.18	5.2		14.7	8.7
40 SK Spot @ 490'		70 Surface		500					8.4	5
					TOTAL					

Available Mix Water Bbl.		Available Displ. Fluid Bbl.		TBG-CSG-D.P.		COLLAR DEPTHS			
SIZE	% EXCESS	DEPTH	SIZE	WGT.	TYPE	DEPTH	SIZE	FLAT	STAKE
			1870	4 1/2	10J				

LAST CASING		PKR-CMT RET-BR PL-LINER		PERF DEPT		TOP CONN.		WELL FLUID	
SIZE	WGT.	TYPE	DEPTH	TOP	IM	SIZE	THREAD	TYPE	WGT

CAL. DISPL. VOL. Bbl		CAL. PSI		CAL. MAX. PSI		OP. MAX. PSI		MAX TBG PSI		MAX CSG PSI		DISPL. FLUID		WATER SOURCE	
TBG	CSG	CSG	TOTAL	BUMP PLUG	TO REV	60 PSI	FLAT	OP	FLAT	OP	TYPE	WGT			

EXPLANATION: TROUBLE SETTING TOOL, HUMPING CSG, PRIOR TO CEMENTING:

PRESSURE RATE DETAIL				EXPLANATION	
TIME HR: MIN.	PRESSURE - PSI PIPE	PRESSURE - PSI ANNULUS	RATE RPM	FLUID TYPE	SAFETY MEETING: CREW U
			3	H ₂ O	TEST LINES
			3	601 Pump	CIRCULATING WELL RIG U
			3	1/2 cement 70 SK's cement @ 1850'	WPS U
			3	H ₂ O Pump	
			3	200H to 490'	
			3	40 cement Pump 40 SK's 490' to Surface	

BUMPED PLUG	PSI TO BUMP PLUG	TEST FLOAT EQUIP.	TOTAL BW PUMPED	PKR CMT IN LINES/INVERTED	PSI LEFT ON CSG	SPOT TOP CEMENT	SER. SUP.	CUSTOMER REP.
Y N		Y N						

