

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

NM-019401

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

Unit M

8. Well Name and No.

Largo Federal 1A

9. API Well No.

3004529150

10. Field and Pool, or Exploratory Area

Blanco Mesa Verde

11. County or Parish, State

San Juan NM

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Bledsoe Petro Corporation

3. Address and Telephone No.

1717 Main Street Suite 5850 Dallas, Texas 75201 214/742-5800

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

(790' FNL 910' FWL Section 11-T27N-R8W

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Production String

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8 5/8"

J-55 24# surface casing set @ 327' cemented w/75 ft³. (60 sks) Portland cement w/2% CaCl circulated to surface.

4-1/2 J-55 10.50# production string set @ 5500' w/DV tool @ 2514' 1st stage cement 528 sks. (945 ft.³) Halliburton Light cement w/ 1/4# sk Flocele and 5# sks Gilsonite followed by 260 sks (325 ft³) Halliburton standard cement. Cement circulated to DV tool.

2nd stage cement 612 sks. (1087 ft³) Halliburton light cement 1/4#/sk Flocele followed by 100 sks. (119 ft³) Halliburton standard cement w/2% CaCl circulated to surface.

14. I hereby certify that the foregoing is true and correct

Signed

Gregg Baiano

Title Petroleum Engineer

Date

9/8/94

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

FARMINGTON DISTRICT OFFICE

BY

Sm