New 1990 DEPARTME	ITED STATES  NT OF THE NOTERIOR 1994  LAND MANAGEMENT	FORM APPROVED Budger Bureau No. 1004-0135 Expires: March 31, 1993  5 Lease Designation and Serial No
Do nor use this form of proposals to drill or to deepen weekly to a different reservoir.		NM-33030 63f Indian, Allonee or Tribe Name
SUBMIT IN TRIPLICATE		Navajo (surface) 7 If Unit or CA, Agreement Designation
Type of Well		N/A
Oil Gas Other		8. Weil Name and No.
2 Name of Operator		Black Hills #1
Texakoma Oil and Gas Corporat	ion (214)701-9106	9. API Well No.
3 Address and Telephone No.		30-045-29190
One Lincoln Centre, 5400 LBJ	Freeway, Suite 500, Dallas, TX 75240	10. Field and Pool, or Exploratory Area
4 Location of Well (Footage, Sec., T., R., M., or Survey I	Description)	Basin Fruitland Coal
1,000' FSL and 1,000' FWL		11. County or Parish, State
S/2 Sec. 25, T-26-N, R-13-W		San Juan County, NM
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION	
	TIPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
X Subsequent Report	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing Water Shut-Off
Final Abandonment Notice	Casing Repair  Altering Casing	Conversion to Injection
	X Other Drill & Complete	Dispose Water
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*		
Spudded well @ 3:00 p.m., MDT, on 10/1/94. Drilled 12-1/4" hole to 130'. Ran 8-5/8" 24# J-55 ST&C to 129.05'. Guide shoe @ 128.05', insert float @ 88.90' and 2 centralizers @ 100' and 20'. Cmt'd w/100 sx (1.18 ft³) stand cmt + 2% CaCl + .25#/sx Flocele. Circ 4 Bbl cmt to surf at 12:30 p.m., MDT, 10/2/94. Drilled Baffle and tested to 1,000 psi. Drilled 7-7/8" hole to 1,365'-TD @ 9:40 a.m., MDT, 10/5/94. Ran open hole logs. Ran 5-1/2" 15.5# J-55 LT&C w/guide shoe @ 1,362', insert float @ 1,323' and 6 centralizers @ 1,343'; 1,283'; 1,207; 1,145'; 1,061'; and 977'. Cmt'd prod string w/180 sx (329 ft³) standard cmt + 2% CaCl + .25#/sx Flocele followed by 100 sx (118 ft³) stand cmt + .6% HALAD-322. Bumped plug to 900 psi @ 8:30 p.m., MDT, 10/5/94. Circ 10 Bbls cmt to surf. Ran GR/CBL/CCL on 10/26/94 from 1,307'-Surface, WLPBTD 1,318'. Perf. Fruitland coal @ 983'-986' (3') 2 SPF; 1,174'-1,196' (22') 6 SPF; 1,200'-1,204' (4') 6 SPF; 1,210'-1,218' (8') 6 SPF; 1,263-1,266' (3') 4 SPF on 10/26/94. Total of 40 holes. Performed foam frac. Ran 2-3/8" tbg to 1,285'± and installed down hole pump.		
Signed Watter Dereyer	Title Drilling Manager	
(This space for Federal or State office use)		AACOTED FAD DEAADS
Approved by Conditions of approval, if any:	Tide	ACCEPTED FOR RECORD
		NOV - 2 1001