UNITED STATES

DEPARTMENT OF THE INTERIOR REGENTED BUREAU OF LAND MANAGEMENT

	rts on Well	- ^{s,} 411:21		
l. Type of Well GAS	()	1000	5. 6.	Lease Number NM-03154 If Indian, All. or Tribe Name
			7.	Unit Agreement Name
Name of Operator MERIDIAN OIL				
3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505)	326-9700		8.	Well Name & Number Ballard #504 API Well No.
	320 3700			30-045-29297
4. Location of Well, Footage, Sec., T, R, M 1450'FNL, 1620'FEL, Sec.15, T-26-N, R-9-W	, NMPM			Field and Pool Basin Fruitland Coal County and State San Juan Co, NM
2. CHECK APPROPRIATE BOX TO INDICATE NATURE	OF NOTICE	REPORT, C	THER	DATA
X Notice of Intent Abandon Recompl Subsequent Report Pluggin Casing Final Abandonment X Alterin Other	etion g Back Repair g Casing	<pre>K_ Change o New Cons Non-Rout Water Sh</pre>	truct ine E ut of	ion Tracturing Ef
 Describe Proposed or Completed Operati 	.ons			
It is intended to alter the approved s well. The new surface casing de				
well. The new surface casing de				
well. The new surface casing de Revisions: Mud Program: Interval Type Wei		e a minimu Fluid Lo	n of	120'. DECEMBE JAN 3 C 1896
well. The new surface casing de Revisions: Mud Program:	epth will b	e a minimu	n of	120'. PEGENTE JAN 3 C 1836 OUL GOML DOM
well. The new surface casing definitions: Mud Program: Interval Type Wei Spud 8.4 Casing Program:	epth will b	e a minimu Fluid Lo No contr	n of	
well. The new surface casing de Revisions: Mud Program: Interval Type Wei 7 Spud 8.4 Casing Program:	epth will b .ght 8.9	e a minimu Fluid Lo No contr	n of	JAN 3 0 1536 OUL GOM, DIN Grade
well. The new surface casing do Revisions: Mud Program: Interval Type Wei 0-120' Spud 8.4 Casing Program: Hole Size Depth Interval Casing 1/4" O-120'	epth will b ght =-8.9 ssing Size 8 5/8"	Fluid Lo No contr Weight 24#	n of ss ol	JAN 3 C 1806 OUL COMP DIN Grade K-55
well. The new surface casing do Revisions: Mud Program: Interval Type Wei 0-120' Spud 8.4 Casing Program: Hole Size Depth Interval Ca 12 1/4" O-120' Cementing Program: 8 5/8" surface casing - 126 sx Class " chloride (148.6 cu.ft. of slurry, 2008)	epth will b	Fluid Lo No contr Weight 24# with 0.25 p	n of ss ol	JAN 3 C 1806 OUL COMP DIN Grade K-55
well. The new surface casing de Revisions: Mud Program: Interval Type Wei 8.4 Casing Program: Hole Size Depth Interval Casing Program: Cementing Program: 8 5/8" surface casing - 126 sx Class Chloride (148.6 cu.ft. of slurry, 2008) Test casing to 600 psi/30 minutes.	epth will b	Fluid Lo No contr Weight 24# with 0.25 p circulate	n of ss ol	JAN 3 C 1806 OUL COMO DIN Grade K-55 Cocle and 2% calcium arface). WOC 12 hours.