In Lieu of Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

☐ Water Shut-Off

☐ Dispose Water

□ Non-Routine Fracturing

☐ Conversion to Injection

(Note: Report results of multiple completion on Well Completion or Recompletion Report and

RECEIVE SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals 98 133 29 1772: 29 Lease Designation and Serial No. NO-G-9602-1300 ON FRANKISH KI 6. If Indian, Allottee or Tribe Name Navajo SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1 Type of Well Well Name and No. ☐ Oil Well **⊠** Gas Well ☐ Other Stacey #1 2 Name of Operator API Well No. Thompson Engineering and Production Corp. 30-045-29396 Address and Telephone No. C/O Walsh Engineering & Production Corp. Field and Pool, or Exploratory Area 7415 East Main Farmington, NM 87402 WAW Fruitland Sand - PC 4 Location of Well (Footage, Sec., T., R., M., or Survey Description) 11 County or Parish, State 835' FSL & 1805' FEL, Sec. 6, T26N, R12W, Unit O San Juan County, NM. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION ☐ Notice of Intent ☐ Abandonment ☐ Change of Plans

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

□ Other

☐ Altering Casing

8/21/96 Spud 8-3/4" surface hole and TD at 140'. Run 3 joints (131') of 7", 20#, J-55 ST&C casing and set at 132' GL. Cemented with 55 sx (65 cu.ft.) of Cl "B" with 1/4# cello-flake/sk. Circulated 5 bbls of cement to surface.

8/23/96 TD 6-1/4" hole at 1260' GL. Run 30 joints (1245') of 4-1/2", 10.5#, J-55, ST&C casing and set at 1244' GL. Cemented with 90 sx (185 cu.ft.) of Cl "B" with 2% metasilicate and 1/4# cello-flake/sk. and 75 sx (89 cu.ft.) of Cl "B" with 1/4# cello-flake/sk. Circulated 6 bbls of cement to surface. Wait on completion.

14.	I hereby certify that the foregoing is true and correct  Signed Paul C. Thompson)	Title	President	Date	08/27/96	-
	(This space for Federal or State office use)			ACCEPT	ED FOR RECORD	
	Approved byConditions of approval, if any:	Title		Date A	UG 3 0 1996	