Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Sudget Bureau No. 1004-

Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No.

NMNM11773

SUNDRY NOTICES ANI	REPORTS	ON	WELLS
--------------------	---------	----	-------

LS - Is All 10: 39 6. If Indian, Allottee or Tribe Name

RECEIVET BLM

Do not use this form for proposals to dri	ll or to deepen or reentry to a different reservoir.			
Use "APPLICATION FO	R PERMIT" for such proposals 070	farmington, N	<u>M</u>	
SUBMIT I	N TRIPLICATE		7. If Unit or CA, Agreement Designation	
1. Type of Well Oil Well Well Othe	CONFIDENTIA	L	8. Well Name and No.	
2. Name of Operator		·	T. W. No. 1	
Redwolf Production, Inc.	ASPENIER	عام. م	9. API Well No.	
3. Address and Telephone No.		30-045-29431		
P. O. Box 5382, Farmington, NN	1 87499 SEP 1 5 199305)	// 326-4125	10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) [CON DIV		Waw Fr. Sand/Basin Fr. Coal		
950' FSL & 1040' FWL 950' FSL & 1040' FWL		11. County or Parish, State		
Section 31, T26N, R11W	ும்றம் அ		San Juan County, New Mexico	
12. CHECK APPROPRIATE BOX(s) T	O INDICATE NATURE OF NOTICE, REPO	ORT, OR OTHER DAT	A	
TYPE OF SUBMISSION	ТҮРЕ С	TYPE OF ACTION		
Notice of Intent	Abandonment		Change of Plans	
X Subsequent Report	Recompletion Plugging Back		New Construction Non-Routine Fracturing	
	Casing Repair		Water Shut-off	
Final Abandonment Notice	Altering Casing		Conversion to Injection	
	X Other Run p	roduction casing.	Dispose Water (Note: Report results of multiple completions on	
13. Describe Proposed or Completed Operations (Clearly	state all pertinent details, and give pertinent date		ell Completion or Recompletion Report and Log form.)	
proposed work. If well is directionally drilled, give su work.)*	· · · · · · · · · · · · · · · · · · ·	•	•	
Pressure tested surface of	casing and BOP to 600 psi for 3	30 min. Held O	K.	
Drilled 6 1/8" hole to 13	98' KB. Ran 33 jts of 4 1/2", 1	.0.5#, J-55 casin	g.	
Casing set at 1397' KB.	PBD of 1354' KB. Cemented	with 85 sx (175	cf) of Class B	
cement containing 2% S	odium Metasilicate and 1/4 #/s	sk cello flakes,		
followed by 100 sx (118	cf) of Class B cement containing	ıg 2% CaCl anı	d	
1/4 #/sk cello flakes. Cir	culated 21 bbls of cement to se	urface.		
14. I hereby certify that the foregoing is true and correct			The state of the s	
Signed Dava J. Welle	uttal Title	Vice-President	Date 9/3/98	
(This space for Federal or State office)				
Approved by	Title	_	SEP 1 0 1998	
Conditions of approval, if any:		A	BUEP ILD.	
			SEP 1 0 1998	