

27		
		X

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. 078091  
Unit Gov. Donahit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Set Production Cag.</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 20, 1959

Well No. B-19 is located 1980 ft. from IXX line and 660 ft. from E line of sec. 27

C NE SE 26N 13W 20N  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Bisti-Gallup San Juan New Mexico  
(Field) (County or ~~Section~~) (State or Territory)

The elevation of the ~~surface~~ Ground level above sea level is 6198 ft.

DETAILS OF WORK


(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled to 5080' KB TD. Conditioned hole and ran 157 joints - 5000' casing, equipped with centralizers, scratchers and Baker float equipment. Casing landed at 5078' KB and cemented with 100 sx 50-50 pozzix with 2% gel. Pumped 10% solution of magophos ahead of cement. Displaced cement to 5007' KB. Bumped plug with 1500 psi. Ran temperature survey, found top of cement at 4740' KB.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company The British-American Oil Producing Company

Address P. O. Box 180  
Denver 1, Colorado



Original Signed by  
By George W. Murphy  
Assistant General Superintendent  
Title \_\_\_\_\_