

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

PHOENIX HYDROCARBONS OPERATING CORPORATION

3. Address and Telephone No.

P O BOX 3638 MIDLAND, TX 79701

915 686-9869

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1845' FSL & 1165' FEL; I; Sec 14; T-27N; R-8W  
20 mi So of Blanco

5. Lease Designation and Serial No.

NMNM 019403

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

LARGO FED #3A

9. API Well No.

30-045-30804

10. Field and Pool, or Exploratory Area

BLANCO MESAVERDE

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing

☒ Other Change cement  
program on prod string

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Upon the recommendation of Halliburton, Phoenix plans to utilize the single stage foamed cementing process to cement the 4-1/2" casing from T.D. to the surface. Phoenix plans to use about 880 sx - 50/50 POZ/STD cement with the first 630 sx foamed to 11.0#/gal density. The final 250 sx will not be foamed. This process should give zonal isolation superior to the two stage process we originally proposed.

14. I hereby certify that the foregoing is true and correct

Signed Phyllis R. Gunter

Title Agent

Date 9/10/02

(This space for Federal or State Office use)

Approved by

Conditions of approval, if any:

Title

Date SEP 13

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side