Submit 3 Copies To Appropriate District Office	Diate of	State of New Mexico		Form C-103 Revised March 25, 1999	
District I Energy, Minerals and Natural Resources 1625 N. French Dr., Hobbs, NM 88240			WELL API NO.	Revised March 23, 1999	
District II	OH CONCEDUATION DIVICION		30-045-311		
1301 W. Grand Ave., Artesia, NM 882 District III	1301 W. Gland Ave., Artesia, Nivi 88210		5. Indicate Type		
1000 Rio Brazos Rd., Aztec, NM 8741	1000 Rio Brazos Rd., Aztec, NM 87410			X FEE	
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505			6. State Oil & C E-3148-10 & VA		
SUNDRY NO	7. Lease Name of	7. Lease Name or Unit Agreement Name:			
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			BLACK	BLACKHILLS 16	
1. Type of Well:					
Oil Well Gas Well X Other  2. Name of Operator			9 Wall No	8. Well No.	
TEXAKOMA OIL AND GAS CORPORATION			8. Well No.	<b>.</b>	
3. Address of Operator				9. Pool name or Wildcat	
5400 LBJ FREEWAY, SUITE	500, DALLAS, TEXASS 75	240	BASIN-FRUITI	LAND COAL (71629)	
4. Well Location					
Unit Letter A: 700' feet from the SOUTH line and 1850' feet from the WEST line					
Section 16	Township 26N	Range 13W	NMPM Co	ounty SAN JUAN	
	,	whether DR, RKB, RT, GR	, etc.)		
6256' GR 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data					
	CK Appropriate Box to If FINTENTION TO:		JBSEQUENT RE		
PERFORM REMEDIAL WORK		ı		ALTERING CASING	
TEMPORARILY ABANDON	☐ CHANGE PLANS	COMMENCE	DRILLING OPNS.	PLUG AND  ABANDONMENT	
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST	<del></del>		
OTHER:		OTHER: DRI	LL TO T.D., LOG, RUN	CASING, CEMENT	
12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or					
recompilation. THIS WELL SPUDDED ON 8-2-02 AND AN 8 ¾" HOLE WAS DRILLED TO 175' KB AND 4 JTS OF NEW 7" 20 PPF J-55 API					
CASING WAS SET AT 170' KB AND CEMENTED TO SURFACE WITH 60 SKS (71 CF)CLASS H W/2% S-001 & ¼ #/SK D-29					
FLUID LOSS @ 15.8 PPG, YIELD 1.18 CF/SK, CIRCULATED 5 BBLS GOOD CEMENT TO SURFACE. ON 8-4-02, INSTALLED					
7" X 4 ½" CASINGHEAD AND ANNULAR BOP, TESTED BOPAND CASING TO 1000 PSIG FOR 15", HELD OK AND THE 7"					
CASING SHOE WAS DRILLED OUT AND A 6 1/4" HOLE WAS DRILLED TO A TOTAL DEPTH OF 1533' ON 8-8-02.  HALLIBURTON'S COMBINATION OPEN LOG WAS RUN INCLUDING THE HIGH RESOLUTION INDUCTION AND					
SPECTRAL DENSITY DUAL-SPACED NEUTRON FOR A LTD OF 1521' KB. ON 8-8-02, 34 JOINTS OF NEW 4 1/2", 10.5 PPF, J-					
55 CASING WAS RUN TO 1521' KB AND CEMENTED TO SURFACE WITH 100 SKS (175 CF) 35/65 POZMIX CLASS G					
CEMENT WITH 2% CACL AND 6% GEL W/ ¼ LB/SK OF CELLOFLAKE AT 12.7 PPG, YIELD 1.75 CF/SK AND TAILED IN WITH 100 SKS (118 CF) OF CLASS G CEMENT W/2% CACL W/¼#/SK CELLOFLAKE, MIXED AT 15.6 PPG, YIELD 1.18					
CU.FT/SK AND DISPLACED					
CIRCULATED 4 BBLS OF GO					
TUBING HEAD, RELEASED	RIG AT 8:00 P.M. 8-8-02. (	COMPLETION OPERATI	ONS SHOULD BEGI	N IN NEXT 60 DAYS.	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.					
SIGNATURE TO MANAGER DATE 08/19/2002					
	TOM SPRINKLE	Telepho	ne No. 972-701-91	)6	
(This space for State Charles	Markey O. Bright	Barrier Co. S.	n in 1888 and a given by the section of the section	AUG 1. 1 2000	
APPPROVED BY TITLE DATE					
Conditions of approval, if any:				<u> </u>	