

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO.  
30-045-31103

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
E-3148-10 AND VA-2551

7. Lease Name or Unit Agreement Name:

BLACKHILLS 16

8. Well No.

2

9. Pool name or Wildcat  
BASIN FRUITLAND COAL

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

TEXAKOMA OIL & GAS CORORATION

3. Address of Operator

5400 LBJ FREEWAY, SUITE 500, DALLAS, TEXAS 75240

4. Well Location

Unit Letter A : 700 feet from the SOUTH line and 1850 feet from the WEST line

Section 16 Township 26N Range 13W NMPM SAN JUAN County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
6256' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

THIS WELL STARTED DRILLING ON AUGUST 2, 2002 USING L&B SPEED DRILL TOOLS AT 8:30 A.M. MDT. AN 8 3/4" HOLE WILL BE DRILLED TO ABOUT 175' AND 7" 20 PPF NEW J-55 CASING WILL BE RUN AND CEMENTED TO SURFACE. THE CASING HEAD AND BOP WILL BE INSTALLED AFTER THE CEMENT HAS SET FOR ABOUT 12 HOURS. AN 6 1/4" HOLE WILL THEN BE DRILLED TO TOTAL DEPTH AND THE WELL LOGGED.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tom Sprinkle TITLE DRILLING MANAGER DATE 8-2-2002

Type or print name TOM SPRINKLE

Telephone No. 972-701-9106

(This space for State use)

APPROVED BY DEPUTY OIL & GAS INSPECTOR, NM TITLE DEPUTY OIL & GAS INSPECTOR, NM DATE AUG - 5 2002

Conditions of approval, if any: