

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-045 <del>31103-00</del> <u>31175</u>
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE
2. Name of Operator TEXAKOMA OIL AND GAS CORPORATION		6. State Oil & Gas Lease No. E-3148-10 & VA-22510 & E-9707
3. Address of Operator 5400 LBJ FREEWAY, SUITE 500, DALLAS, TEXAS 75240		7. Lease Name or Unit Agreement Name:  BLACKHILLS 16
4. Well Location  Unit Letter <u>A:</u> <u>715'</u> feet from the <u>NORTH</u> line and <u>715'</u> feet from the <u>EAST</u> line  Section <u>16</u> Township <u>26N</u> Range <u>13W</u> NMPM County <u>SAN JUAN</u>		8. Well No.  3
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 6230' GR		9. Pool name or Wildcat BASIN-FRUITLAND COAL (71629)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

THIS WELL SPUDDED ON 10-4-02 AND AN 8 3/4" HOLE WAS DRILLED TO 175' KB (5' GL TO KB) AND 4 JTS OF NEW 7" 20 PPF J-55 API CASING WAS SET AT 170' KB (165' GL) AND CEMENTED TO SURFACE WITH 65 SKS (76.7 CF) CLASS B W/2% CACL2 & 1/4 #/SK CELLOFLAKE @ 15.6 PPG, YIELD 1.18 CF/SK, CIRCULATED 5 BBLS GOOD CEMENT TO SURFACE, DISPLACED WITH 5 BW, PD AT 3:30 PM 10-4-02, WOC OVERNIGHT. INSTALLED 7" X 4 1/2" 2M CASINGHEAD AND 2M ANNULAR BOP, TESTED BOP TO 1000 PSIG FOR 15", HELD OK. DEVIATION SURVEYS AT 175'-1/4 DEGREE, AT 730'-1/2 DEGREE, PREPARE TO DRILL AHEAD WITH 6 1/4" BIT TO TOTAL DEPTH.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tom Sprinkle TITLE DRILLING MANAGER DATE 10/07/2002

Type or print name TOM SPRINKLE Telephone No. 972-701-9106

(This space for Signature)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

Conditions of approval, if any: