

AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

Tamamaco Oil Corporation
(Company or Operator) (Lease)

Well No. 27-B, in NW 1/4 of NE 1/4, of Sec. 27, T. 28 N., R. 1 E, NMPM.
Pool, Rio Arriba County.
Well is 330' feet from North line and 1501' feet from East line
of Section 27. If State Land the Oil and Gas Lease No. is
Drilling Commenced July, 1961 Drilling was Completed August 27, 1961
Name of Drilling Contractor Star Drilling Company, Howard Lynn
Address Farmington, New Mexico
Elevation above sea level at Top of Tubing Head 7102' The information given is to be kept confidential until
, 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from 300' to less than 390' feet.
No. 2, from 711' to ? feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
7"	22 ¹ / ₂	New	389.64'	Tex. Pat.			surface
4 ¹ / ₂ "	9 ¹ / ₂	New	831'	Tex. Pat.			Gas string.

MUDDING AND CEMENTING RECORD


SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
7-7/8"	7"	389.64'	none			
6-1/2"	4 1/2"	1213'	none			
3-3/4"	none	drilled to 1928'. Filled hole with heavy mud, then pumped 20				skts cement at 977'
6 1/2"	4 1/2"	831'	30 sks.	Dowell	very heavy	gas string.
	and again	831'	60 sks.			

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

After drilling out plug at 831', spotted two bbls of M.C.A. 15% acid. Then swabbed out, no shows.

Result of Production Stimulation none



If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

Rotary tools were used from 0 feet to 1948' feet, and from _____ feet to _____ feet.
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

Length of Time Shut in.....

T. Anhy.....	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....	T. Silurian.....	T. Kirtland-Fruitland.....
B. Salt.....	T. Montoya.....	T. Farmington.....
T. Yates.....	T. Simpson.....	T. Pictured Cliffs.....
T. 7 Rivers.....	T. McKee.....	T. Menefee.....
T. Queen.....	T. Ellenburger.....	T. Point Lookout.....
T. Grayburg.....	T. Gr. Wash.....	T. Mancos.....
T. San Andres.....	T. Granite.....	T. Dakota.....
T. Glorieta.....	T.	T. Morrison.....
T. Drinkard.....	T.	T. Penn.....
T. Tubbs.....	T.	T.
T. Abo.....	T.	T.
T. Penn.....	T.	T.
T. Miss.....	T.	T.

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
692'			Gallup				
1362'			San Juan				
1874			Dakota				

Company or Operator Townsend Oil Corporation
Name H. B. Piller

Date April 26, 1963 (Date)
Address 409 Alamo N.E., Albuquerque, N.M.
Title President