

# WELL RECORD


AREA 640 ACRES  
LOCATE WELL CORRECTLY

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

Tampana Oil Corporation  
(Company or Operator)

(Lease)

Well No. 27-B, in NW 1/4 of NE 1/4, of Sec 27, T. 28 N., R. 1 E, NMPM.

Pool, Pio Arriba

County.

Well is 330' feet from North line and 1501' feet from East line

of Section 27. If State Land the Oil and Gas Lease No. is

Drilling Commenced July, 1961. Drilling was Completed August 27, 1961

Name of Drilling Contractor Star Drilling Company, Howard Lynn

Address Farminaton, New Mexico

Elevation above sea level at Top of Tubing Head 7102'. The information given is to be kept confidential until  
19

## OIL SANDS OR ZONES

No. 1, from to No. 4, from to  
No. 2, from to No. 5, from to  
No. 3, from to No. 6, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 300' to less than 390' feet.  
No. 2, from 711' to ? feet.  
No. 3, from to feet.  
No. 4, from to feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
7"	22#	New	389.64'	Tex. Pat.			surface
4 1/2"	9 1/2#	New	831'	Tex. Pat.			Gas string.

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
7-7/8"	7"	389.64'	none			
6-1/2"	4 1/2"	1213'	none			
3-3/4"	none	drilled to 1910'	filled hole with heavy mud, then pumped 20 bbls cement at 977'			
6 1/2"	4 1/2"	831'	20 bbls	Dowell	very heavy	gas string.

and again

831'

60 bbls

## RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

After drilling out plug at 831' spotted two bbls of M.C.A. 15% acid. Then swabbed out, no shows.

