

(SUBMIT IN TRIPLICATE)

Indian Agency .....

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Jicarilla Agency

Allottee .....

Lease No. 260

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	X	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 22

19 62

Jicarilla 4-26

Well No. 5 is located 990 ft. from S line and 790 ft. from E line of sec. 26

SE $\frac{1}{4}$  of SE $\frac{1}{4}$ , Sec. 26

23N

1W

R2E

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

Boulder-Juarez

Rio Arriba

New Mexico

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is 7191 ft. (246.)

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Notice is hereby given of intention to drill the Jicarilla 4-26 #5 to a total depth of approximately 3000 feet with rotary tools. 11" surface hole will be drilled to 100 feet where 100 ft of 9-5/8", 36#/ft., J-95, STC surface casing will be landed & cemented w/cement to surface. 8-3/4" hole will be drilled below surface casing with mud to approximately 3000 feet, where logs will be run. 9 1/2", 140#/ft., J-95, STC new casing will be set & cemented at 3000 feet with 200 cu. cement. Drilling will be continued to total depth substituting air for drilling fluid. Primary objective is the Gallup formation. A 4" slotted flush joint liner will be set at total depth if commercial production is obtained.

ILLEGIBLE

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Standard Oil Company of Texas, A Division of California Oil Company

Address Denver "E"

Houston, Texas

By

J. L. Rowland

Title

District Engineer

