## NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

## MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Poo	l Blenco			Fo	rmation	Ne	sa Verde		_County_	Rie Ar	rriba
Ini	tial	·	Annual			Spec	cial		_Date of	Test	9-16-58
Company PACIFIC ECRIPHEST PIPELIE			Lease San Juan 28-4			28-4	We	11 No	18-31		
Uni	t <u><b>M</b></u> S	Sec. <u>31</u>	Twp .	261	Rg	e. 4	Purc	haser			
Cas	ing 53" W	It	I.D	•	Se	t at 4	<b>120'</b> Pe	rf <b>597</b>	0'	To	530'
Tub	ing <b>1-1/4"</b> W	it. 2.4	I.D		Se	t at <b>6</b>	<b>510'</b> Pe	rf		То	
Gas	Pay: From_		То		L		cG <b>.650</b>		- <del> </del>	_Bar.Pr	ess. 19
Pro	ducing Thru:	Casi	ng		<u>r r</u> Tu	bing		Type We	:11	Single	
Date	e of Complet	ion:			Type Single-Bra Packer Reser			gle-Brade Reservo	denhead-G. G. or G.O. Dual voir Temp.		
					<del></del>		ED DATA		- '		
Tes	ted Through	(Pr <i>blik</i>	<b>∤∤)</b> (Ch	oke)	(Meteri)			7 days	Type Ta	ps	
			ow Dat		<del></del>		Tubing		Casing		T
No.	(Prover) (Line)	(Chok	e) P		Diff.	Temp.					Duration of Flow
	Size	Siz	e	psig	h <sub>w</sub>	°F.	psig	°F.	psig	°F∙	Hr.
SI l.		3/1	Litt	L8s		. 66°	916 551		1131	660	3 brea
2 <b>.</b> 3•											
4. 5.		<u> </u>									
No.	Coefficient (24-Hour) √ h <sub>w</sub> H		$\sqrt{\mathtt{h_{w}p_{f}}}$	Pressure		FLOW CALCULATION Flow Temp. Factor Ft		Gravity Factor <sup>F</sup> g	Factor F <sub>pv</sub>	or	@ 15.025 psia
1. 2.	12.3650			1497		-9943		9608	1.949		6159
3. 4. 5.											
5.				工							
ravi	Liquid Hydro ity of Liqui		carbon	s_e-s)_		cf/bbldeg.	-	Speci Speci <sup>P</sup> c——		ity Flo	arator Gas wing Fluid 1306.4
No.	P <sub>w</sub> Pt (psia)	$P_{\mathbf{t}}^2$	F <sub>C</sub> Q		$(F_cQ)^2$	(F	e <sup>-3</sup> )	563 <sub>Pw</sub> 2	• P <sub>c</sub> -P <sub>w</sub>	C	al. Pw Pw Fc
$\frac{1}{2}$ .								317.0	959.4		1.32
1. 2. 3. 4.											
<del>4.</del> 5.						<del>-  </del>					
COMI ADDI AGEN WITN	plute Potent PANY PAGE RESS NO W NT and TITLE NESSED PANY	MORTON	PI VAY	a red n	den. I	RATION ov Mexic Engine	ř	75/ 1.231	<u> </u>		
						Мля	ARKS		KL SE OIL	P2519	COMIN

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871. Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (Pw). MCF/da. @ 15.025 psia and 600 F.
- $P_c$  72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
- Pw- Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mathbf{W}}^{\perp}$  Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If  $P_W$  cannot be taken because of manner of completion or condition of well, then  $P_W$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_+$ .

OIL CONSERVATION COMMISSION AZTEC DISTRICT OFFICE No. Copies Received									
DISTRICOHON									
Cperator	NO.								
Santa Fa									
Coole had solve	***************************************								
The second of th									
F. No.									