

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other P&A

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FSL - 2310' FEL
Sec. 23, T28N, R1W, NMPMFORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

Jic. Tribal Contract #241

6. If Indian, Allottee or Tribe Name

Jicarilla

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Boulder 10

9. API Well No.

30-039-07252

10. Field and Pool, or Exploratory Area

Boulder Mancos

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged well as follows:

1. Perforate Gallup @ 3494'.
2. Spot 59 cu. ft. Class B cement plug with 3% CaCl at 3516'. Wait on cement 2 hrs. Attempt to load hole with 140 bbls water. Wouldn't load.
3. Ran 4 1/2" cement retainer set @ 3274'. (Approval by telephone from Robert Kent, BLM)
4. Pump 59 cu. ft. Class "B" neat cement through retainer. Left 60' cement on top of retainer.
5. Spot 24 cu. ft. Class B cement plug across liner top at 2860'. Liner top plug 2779' - 2910'.
6. Spot 35 cu. ft. Class B cement plug across Mesa Verde from 2164' - 2318'.
7. Perforate below surface casing @ 178'.
8. Cement down 7" casing and through bradenhead to surface with 105 cu. ft. Class B + 4% gel.

Job complete 7-2-93.

14. I hereby certify that the foregoing is true and correct

Signed

John Alexander

Title Operations Manager

Date 7/13/93

(This space for Federal or State office use)

Acting

AREA MANAGER

Approved by SHIRLEY MONDY

Title

RIO PUERTO RESOURCE AREA

Date SEP 10 1993

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOCD