

8-3-60

F.Loc. 1700/S; 1050/W Elev. 6090 GL Spd. 5 1/2 Comp 8-15-60 to 5100 PB
 Casing S.10-3 1/4 @ 165 W 125 Sx. Int. 7-5/8 @ 2800 W 300 Sx. Pr. 2751 - 5095 @ W Sx. T. 1 1/4 @ 2723
 Csg.Perf. 2706-2740 Prod. Stim.
 I.P. 1124 AOF BO/D MCF/D After 3 Hrs. SICP 987 PSI After 73 Days GOR Grav. 1st Del. 12-2-5-6-0

T
R
A
N
S

TOPS		NITD	X	Well Log	TEST							DATA
Kirtland	1972	C-102	X	Plat	X	Schd.	PC	Q	PW	PD	D	Ref. No.
Fruitland	2435	C-103	X	Electric Log								#6094
Pictured Cliffs	2705	C-104		C-110								#6564
Cliff House	4340			C-122	X							
Menefee	4408	Ditr		Dfa								
Point Lookout	4907	Datr		Dac								#7252
Mancos	5035	PT		Remarks								
Gallup												
Sanostee												
Greenhorn												
Dakota												
Morrison												
Entrada												

P
 0 Jan. | Feb. | Mar. | Apr. | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec. |