


State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well GAS 2. Name of Operator BURLINGTON RESOURCES OIL & GAS COMPANY 3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9780 4. Location of Well, Footage, Sec., T, R, M 1190' FSL, 1750' FWL, Sec. 25, T-28-N, R-5-W, NMPM, Rio Arriba County	API # (assigned by OCD) 30-039-07306 5. Lease Number Fee 6. State Oil&Gas Lease # Lease Name/Unit Name San Juan 28-5 Unit 7. Well No. 43 8. Pool Name or Wildcat Blanco Mesaverde 9. Elevation:
---	---



Type of Submission	Type of Action
☐ Notice of Intent	☐ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☒ Other - Pay add
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut off
	☐ Conversion to Injection

13. Describe Proposed or Completed Operations

- 5-10-01 MIRU. TIH w/2 3/8" gauge ring to 5865'. TOOH. TIH w/CIBP, set @ 5850'. TOOH. Load tbgs w/36 bbl 2% KCl wtr. PT tbgs to 1000 psi, OK. TIH, ran CBL-CCL-GR @ 3850-5843', TOC @ 4116'. TOOH. PT csg to 4500 psi, OK. SDON.
- 5-11-01 TIH, perf Cliff House/Menefee w/1 SPF @ 5488, 5490, 5504, 5514, 5516, 5532, 5563, 5590, 5644, 5654, 5684, 5692, 5709, 5726, 5756, 5770, 5795, 5820, 5843' w/19 0.24" diameter holes total. WO frac crew.
- 5-12-01 Acidize w/10 bbl 15% HCl. Frac Cliff House/Menefee w/1011 bbl 20# linear gel, 989,935 SCF N2, 45,000# 20/40 Brady sd. TOOH. TIH w/CIBP, set @ 5270'. PT CIBP to 4500 psi, OK. Perf Lewis w/1 SPF @ 4715, 4717, 4720, 4722, 4725, 4865, 4867, 4870, 4872, 4875, 4990, 4992, 4995, 4997, 5000, 5045, 5228, 5230, 5240, 5242' w/20 0.24" diameter holes total. Acidize w/10 bbl 10% acetic acid. Frac Lewis w/615 bbl 20# linear gel, 1,239,495 SCF N2, 45,000# 20/40 Brady sd. CO after frac.
- 5-13-01 Blow well & CO.
- 5-14-01 Blow well & CO. ND BOP. NU WH. RD. Rig released.
- 8-6-01 MIRU. TIH w/down hole mill. Test down hole motor w/wtr, OK. Tag frac plug @ 5270'. Establish circ. Mill out frac plug. Circ hole clean. TOOH w/motor. SDON.
- 8-7-01 TIH w/motor to 5850'. Establish circ. Drill out frac plug @ 5850'. TIH. Circ hole clean to 5853'. TOOH w/motor. Blow well & CO. RD.

SIGNATURE *Steven N. Hayden* Regulatory Supervisor August 8, 2001

no
(This space for State Use)

Original Signed by STEVEN N. HAYDEN DEPUTY OIL & GAS INSPECTOR, DIST. 3
Approved by _____ Title _____ Date AUG 10 2001

K