

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office New Mexico  
Lease No. 03682  
Unit San Juan 20-4 Unit  
14-00-001-933

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	<input type="checkbox"/>
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL		<input type="checkbox"/>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 10-30 is located 1650 ft. from [N] line and 50 ft. from [E] line of sec. 30  
Sec. 30 (1/4 Sec. and Sec. No.) 20 N (Twp.) 4 (Range) 100-0-0 (Meridian)  
Blanco A.V. (Field) Rio Arriba (County or Subdivision) New Mexico (State or Territory)


The elevation of the derrick floor above sea level is 650 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spud date 7-10-58.  
On 7-12-58. Total Depth 255'.  
Run 7 joints 10 1/4", 32.75#, spiral weld casing (202') set at 232' with  
200 sacks regular cement, 50 cu. ft. stratacrete/100 sk cement, circulated  
to surface.

Held 500# for 30 minutes.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company  
Address Box 291  
Farmington, New Mexico  
By Original Signed D. C. Johnston  
Title Petroleum Engineer

