
Form 9-381 a (Feb. 1951)



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

New Mexico Land Office 03862 Lease No. Unit San Juan 26-4 Unit

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF.	
NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO TEST WATER SHUT-OFF. NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.		SUBSEQUENT REPORT OF SHOOTING OR AGADIZING.	
NOTICE OF INTENTION TO SHOOT OF		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
(INDICA	TE ABOVE BY CHECK MARK	NATURE OF REPORT, NOTICE, OR OTHER DATA)	
		September 13 , 19 61	
/ell No. 27 is locat	edft. from_	S line and ft. from W line of sec.	
.W. Section 19	28- H 4-N	N.M.P.M.	
(1/4 Sec. and Sec. No.)		Range) (Meridian)	
Lanco Hosa Verde (Field)	Rio Arribe		
		Subdivision) (State or Territory)	
pudded 9-6-61.	ing points, and all oth	, weights, and lengths of proposed casings; indicate mudding jobs, cement- ner important proposed work)	
pudded 9-6-61. m 9-6-61 Total Depth joints 9 5/8" 32.30#, 100 aks cament, 25 HA- /8# Flocels/ak. Did	320'. Run 10 E-40 casing (30 5, 1/4 cu.ft. S not circulate,	3') set at 315' with	
pudded 9-6-61. m 9-6-61 Total Depth cints 9 5/8" 32.30f, 00 ske cament, 25 HA-	320'. Run 10 E-40 casing (30 5, 1/4 cu.ft. S not circulate,	3') set at 315' with trate-Crote"6"/ak., as HA-5, 1/8# SEP1 8 1961 CON. COM.	
pussed 9-6-61. n 9-6-61 Total Depth oints 9 5/8" 32.30f, 00 ske cement, 25 HA- /8# Flooels/sk. Did locals/sk. Held 600f	320'. Run 10 H-40 casing (30 5, 1/4 cu.ft. S not circulate, c /30 minutes.	3') set at 315' with trata-Crete"6"/sk., ament w/50 ske regular, 25 HA-5, 1/8#	
pushed 9-6-61. n 9-6-61 Total Depth oints 9 5/8" 32.30%, 00 sks cement, 25 Ha- /8% Floosle/sk. Did locals/sk. Hald 600%	320'. Run 10 E-40 casing (30 5, 1/4 cu.ft. S not circulate, c	3') set at 315' with trata-Crete"6"/sk., sment w/50 ske regular, 25 HA-5, 1/8# SEP1 8 1961 OIL CON. COM. DIST. 3	
pudded 9-6-61. n 9-6-61 Total Depth oints 9 5/8" 32.30#, 30 ske cement, 25 Ha-/8# Flooels/sk. Did locals/sk. Bald 600#	320'. Run 10 H-40 casing (30 5, 1/4 cu.ft. S not circulate, c /30 minutes.	3') set at 315' with trata-Crete"6"/sk., sment w/50 ske regular, 25 HA-5, 1/8# SEP1 8 1961 OIL CON. COM. DIST. 3	
understand that this plan of work mpany 1. 9-6-61 Total Depth oints 9 5/8" 32.30%, 30 aks cement, 25 Ha- /8% Flocels/sk. Did locals/sk. Hald 600%	320'. Ren 10 H-40 casing (30 5, 1/4 cu.ft. S not circulate, o / 30 minutes.	3') set at 315' with trata-Crete"6"/sk., sment w/50 ske regular, 25 HA-5, 1/8# SEP1 8 1961 OIL CON. COM. DIST. 3	
pudded 9-6-61. 1 9-6-61 Total Depth bints 9 5/8" 32.304, 20 ake cement, 21 HA-/84 Floorie/ak. Did locale/ak. Bald 600/11 Pasc Matar mpany 11 Pasc Matar dress 1808990	320'. Ren 10 H-40 casing (30 5, 1/4 cu.ft. S not circulate, o / 30 minutes.	3') set at 315' with trate-Crete"6"/ak., SEP18 1961 OIL CON. COM DIST. 3 riting by the Geological Survey before operations may be commenced.	