

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Santa Pe Land Office 079290-A Lease No. Unit San Juan 28-7 Unit 14-08-001-459

NOTICE OF INTENTION TO DRIL	L	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHAN		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZ	ING
NOTICE OF INTENTION TO TEST			· · · · · · · · · · · · · · · · · · ·
NOTICE OF INTENTION TO RE-D	RILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPA	AIR
NOTICE OF INTENTION TO SHOO			
NOTICE OF INTENTION TO PULL			
NOTICE OF INTENTION TO ABAN	DON WELL	Water Fracture	X
(1)	IDICATE ABOVE BY CHECK M	IARK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
		July	10 , 1956
Vell No. <u>51</u> is l	ocated <i>3</i> 90 ft. fr 281	rom. $\begin{cases} N \\ S \end{cases}$ line and 1850. ft. from $\begin{cases} E \\ S \end{cases}$ line	e of sec. 24
(14 Sec. and Sec. No.)	(T₩p.)	(Range) (Meridian)	
ilanco		kio Arriba Nev X	oxico
(737.7.3)	(Com	nty or Subdivision) (State or Terri	tory)
ta:e names of and expected dep	rick floor above sea DET ths to objective sands; show ing points, and	level is 6580 ft. FAILS OF WORK w sizes, weights, and lengths of proposed casings; indicate all other important proposed work)	mudding jobs, cement-
he elevation of the der	rick floor above sea DET ths to objective sands; shoving points, and 5650	level is 6560 ft. FAILS OF WORK we sizes, weights, and lengths of proposed casings; indicate all other important proposed work) fractured Point Lookout perforate the contract of the contr	mudding jobs, cement- ed int. 5510-2
he elevation of the der ta: names of and expected dep 7-4-56 T.D. C.O. to 5-68-80, 5512-24, 1 1-4-56 T.D. B.P. 0 1120-32, 5146-56 w 1400, avg. tr. pr. 7-5-56 T.D. B.P. 0 141 66,000 gala.	DET the to objective sands; showing points, and to 5650. Water in the 55,800 cal. Injection rate 5240. Water in the 55,350 cals. 2000. Inj. re 5050. Water in the 50,000.	level is 6580 ft. FAILS OF WORK we sizes, weights, and lengths of proposed casings; indicate all other important proposed work) fractured Point Lookout perforat	mudding jobs, coment- ced int. 5510-2 cressure 3000#, cns. int. 5078-90, #, max. pr. lons. int. 4980-5000
he elevation of the der tate names of and expected dep 1-4-56 T.B. C.O. tr 1-68-80, 5512-24, 1 1-4-56 T.B. B.P. © 1-120-32, 5146-56 w 1-5-56 T.B. B.P. ©	DET the to objective sands; showing points, and the points, and the points, and the points, and the points of the points of the points. Jaho . Water in the points of the	level is 6580 ft. FAILS OF WORK we sizes, weights, and lengths of proposed casings; indicate all other important proposed work) fractured Point Lookout perforate the sector & 60,000 sand. Maximum perforate to the sector of	mudding jobs, coment- red int. 5510-2 ressure 3000#, cns. int. 5078-90, #, max. pr. lons. int. 4980-5000 , Avg. ir. pr.
he elevation of the der tate names of and expected dep 7.4-56 T.D. C.O. to 5.68-80, 5512-24, 1 6.68-80, 5512-24, 1 6.68-80, 5512-24, 1 6.68-80, 5512-24, 1 6.68-80, 5512-56 w 6.68-80, 5	DET the to objective sands; showing points, and the points, and the points, and the points, and the points of the points of the points. Jaho . Water in the points of the	level is 6580 ft. FAILS OF WORK we sizes, weights, and lengths of proposed casings; indicate all other important proposed work) fractured Point Lookout perforate the sector & 60,000 sand. Maximum perforate to the sector of	mudding jobs, coment- red int. 5510-2 ressure 3000#, cns. int. 5078-90, #, max. pr. lons. int. 4980-5000 , Avg. ir. pr.