

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1075' FSL, 800' FEL, Sec.12, T-28-N, R-4-W, NMPM

5. Lease Number
SF-079727A

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name
San Juan 28-4 Unit

8. Well Name & Number
San Juan 28-4 U #7

9. API Well No.
30-039-07453

10. Field and Pool
Choza Mesa Pict.Cliffs

11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

8-10-95 MIRU. ND WH. NU BOP. SDON.

8-11-95 TIH w/1 13/16" gauge ring to 4060'. Tag fill. POOH. Perf 2 sqz holes in tbq @ 4050'. TOOH. TOOH w/133 jts 2 3/8" tbq. TIH w/5 1/2" gauge ring to 3880'. TOOH. TIH w/5 1/2" cmt retainer, set @ 3843'. Load csg w/38 bbl wtr, circ hole clean. PT csg to 500 psi/5 min, OK. Plug #1: pump 63 sx Class "B" cmt below cmt retainer into Pictured Cliffs open hole. pump 56 sx Class "B" cmt above cmt retainer, TOC @ 3362'. TOOH. TIH, perf 3 sqz holes @ 2288'. Establish injection. TIH w/5 1/2" cmt retainer, set @ 2213'. SD for weekend.

8-14-95 Establish injection. Plug #2: pump 38 sx Class "B" cmt outside csg @ 2188-2288'. Pump 9 sx Class "B" cmt above cmt retainer, TOC @ 2136'. POOH. TIH, perf 3 sqz holes @ 299'. Establish circ out bradenhead w/12 bbl wtr. Plug #3: pump 115 sx Class "B" cmt from 299' to surface. Circ 1 bbl cmt to surface. WOC. ND BOP. Cut off WH. Install dry hole marker w/8 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 8-14-95.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 8/22/95

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any: _____

APPROVED

NMOCD