Form 9-331 (May 1963)	UNITED STATES DEPARTMENT OF THE INTER GEOLOGICAL SURVEY	SUBMIT IN TRIPLICATES (Other instructions on re- COR verse side)	Form approved, Budget Burght No. 42 41424, 5. Lease designation and search No. SF 078498
SUN (Do not use this	IDRY NOTICES AND REPORTS form for proposals to drill or to deepen or plug Use "APPLICATION FOR PERMIT" for such	ON WELLS back to a different reservoir. proposals.)	6. IF INDIAN, ALLOTT SE OR TRIBE NAME
1. O'L GAS WELL OTHER 2. NAME OF OPERATOR VELL CONTROL OF OPERATOR OTHER			San Juan 28-7 Unit 8. FARM OR LEASE NAME
El Paso Natural Gas Company 3. ADDRESS OF OPERATOR			San Juan 28-7 Unit
PO Box 990, Farmington, NM 87401 1 ISCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) It surface 800'S, 800'W			135 10. FIELD AND POOL, OR WILDCAT Basin Dakota 11. SEC., T., R., M., OR BLK, AND SURVEY OR AREA Sec. 27, T-28-N, R-7-W
14. PERMIT NO.	15. FILVATIONS (Show whether I	DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
	6165'GL Check Appropriate Box To Indicate		Rio Arriba New Mexico
TEST WATER SHUT-O PRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)	MULTIPLE COMPLETE PRACTURE TREATMENT X ALTERING CASING ABANDON* CHANGE PLANS (Other) (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) on completed operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any fixed is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-		
	set at 7312'. Float collar set at 7304'. Cemented with 650 cu.ft. cement. WOC 18 hours. Top of cement at 2710'.		
4-2-73	PBTD 7304'. Tested casing to 4000#-OK. Perf'd first stage 7206-12', 7220-26', 7236-42' and 7259-65' with 18 shots per zone. Frac'd with 35,000# 40/60 sand and 38,108 gallons treated water. Dropped three sets of 18 balls each. Flushed with 4872 gallons. Perf'd second stage 7032-40', 7052-64', and 7152-68' with 18 shots per zone. Frac'd with 28,000# 40/60 sand and 28,964 gallons treated water. Dropped two sets of 18 balls each. Flushed with 4788 gallons.		

18. I hereby cortify that the forexolog is true and correct signed OIL CON. COM.

Petroleum Engineer CIST. 3DATE April 12, 1973

This space for Federal or State office use)

PPROVED BY TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

APR 10 1973