14. PERMIT NO.

SUBMIT IN TRIPLICATE* (Other instructions on verse side)

Form approved.

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

	GEOLOGICAL SURVEY	SF 078496-A
	SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTER OR TRIBE NAME
ī.	OIL GAS X OTHER	San Juan 28-7 Unit
2.	El Paso Natural Gas Company	San Juan 28-7 Unit
8.	PO Box 990, Farmington, NM 87401	9. WELL NO. 188
4.	LOCATION OF WELL (Report location clearly and in accordance with an State requirements 1974 See also space 17 below.) At surface 810'S, 1750'W OIL' CON. COM. DIST. 3	10. FIELD AND FOOL, OR WILDCAT Basin Dakota 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 26, T-28-N, R-7-W NMPM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data 16.

15. ELEVATIONS (Show whether DF. RT, GR, etc.)

6625'GL

NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:				
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)		PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON® CHANGE PLANS		WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (Note: Report res Completion or Reco	X X Sults of muompletion	REPAIRING WELL ALTERING CASING ABANDONMENT* altiple completion on Wel Report and Log form.)	
			. 11	-ut disally and also monthsont de	tog ingluc	line artimated data of st	artina

- SUBBLE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)
 - TD 3615'. Ran 114 joints 7", 20#, J-55 intermediate casing, 3604' set 10-8-73 at 3615'. Cemented with 255 cu.ft. cement. WOC 12 hours, held 1200#/30 min. Top of cement at 2300'.
 - TD 7808'. Ran 247 joints 4 1/2", 11.6 and 10.5#, J-55 production casing, 10-14-73 7797' set at 7808'. Float collar set at 7802'. Cemented with 653 cu.ft. cement. WOC 18 hours. Top of cement at 5050'.
 - PBTD 7802'. Tested casing, held 4000#-OK. Perf'd 7547', 7564', 12-18-73 7659', 7661', 7688', 7702', 7736' and 7739' with one shot per zone. Frac'd with 50,000# 40/60 sand and 73,390 gallons treated water. No ball drops. Flushed with 5200 gallons water.

18. I hereby certify that the foregoing is true and correct SIGNED	TITLE -	Drilling Clerk	January	3, 1974
(This space for Federal or State office use)	7			
APPROVED BY	TITLE .		DATE	<u>, 4) </u>