Form	9-331	
(May	1963)

UNITED STATES DEPARTMENT OF THE INTERIOR

SUBMIT IN TRIPLICATE*
(Other instructions on re-

Form approved.
Budget Bureau No. 42-R1424.

(100.)	DEPARTMENT OF THE INTERIOR verse alde) GEOLOGICAL SURVEY			5. LEASE DESIGNATION AND SERIAL NO. SF078417		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)			6. IF INDIAN, ALLOTTE			
1.				7. UNIT AGREEMENT NA		
OIL GAS WELL OTHER			San Juan 28-7 Unit			
2. NAME OF OPERATOR			8. FARM OR LEASE NAME			
El Paso Natural Gas Company			San Juan 28-7 Unit			
3. ADDRESS OF OPERATOR			9. WELL NO.			
P. O. Box 990, Farmington, NM 87401			239			
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*			10. FIELD AND POOL, OR WILDCAT			
See also space 17 below.) At surface			Basin Dakota			
2080'S, 950'W			Sec. 17, T-28-N, R-7-W N.M.P.M.			
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, e.c.)		12. COUNTY OR PARISE	1 13. STATE			
11, 124,111		6691' GL		Rio Arriba	New Mexico	
16.	Check Ap	propriate Box To Indicate	Nature of Notice, Report, or (Other Data		
	NOTICE OF INTEN	TION TO:	SUBSEQ	SUBSEQUENT REPORT OF:		
TEST WATER		PULL OR ALTER CASING	WALLE SHOT OF	X REPAIRING ALTERING O	·	
FRACTURE TI			SHOOTING OR ACIDIZING	ABANDONME	NT*	
SHOOT OR AC		ABANDON*	(Other)	-		
REPAIR WELL	L	CHANGE PLANS	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			
(Other)						
17. DESCRIBE PRO proposed v nent to this	work. If well is direction	RATIONS (Clearly state all pertu- mally drilled, give subsurface k	nent details, and give pertinent dates ocations and measured and true vertic	al depths for all marker	s and zones perti-	

- O5-11-75 TD 3753'. Ran 91 joints 7", 20#, J-55 intermediate casing, 3741' set at 3753'. Cemented with 299 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 2200'.
- 05-16-75 TD 7844'. Ran 239 joints 4 1/2", 10.5 and 11.6#, J-55 production casing, 7834' set at 7844'. Float collar set at 7837'. Cemented with 632 cu. ft. cement. WOC 18 hours, top of cement at 2650'.
- O6-24-75 Located leak at bottom of casing. Set B. P. above leak at 7831'. PBTD 7831'. Tested casing to 4000#, OK. Perd'd 7630', 7642', 7656', 7730', 7761', 7792', 7806', 7816', 7830' with 1 shot per zone. Frac'd with 70,000#--40/60 sand and 72,618 gallons treated water. No ball drops. Flushed with 5250 gallons water.

RECEIVE			
81GNED SIGNED SI	rilling Clerk	DATE	June 27, 1975
(This space for Federal or State office use) APPROVED BY CONDITIONS OF APPROVAL, IF ANY:		DATE	