

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas well ☐ other ☐ dry hole ☐
2. NAME OF OPERATOR
Jerome P. McHugh
3. ADDRESS OF OPERATOR
Box 208, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: ~~1196~~¹¹¹⁰' FNL - 1560' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- | | |
|--------------------------|--------------------------|
| REQUEST FOR APPROVAL TO: | |
| TEST WATER SHUT-OFF | <input type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> |
| MULTIPLE COMPLETE | <input type="checkbox"/> |
| CHANGE ZONES | <input type="checkbox"/> |
| ABANDON* | <input type="checkbox"/> |
| (other) | |

SUBSEQUENT REPORT OF

REPORT OF **RECEIVED**
JAN 1 3 1985

JAN 17 1985 (NOTE)

OIL CON. DIV.
DIST. 3

5. LEASE Contract 84
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Jicarilla Apache
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
June
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Blanco Mesaverde *Gavilan*
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 28 T28N R3W
12. COUNTY OR PARISH Rio Arriba
13. STATE NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6935' GL 6947' RKB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-10-79 This well was plugged and abandoned in the following manner:

1. Spotted 55 sx (64.9 cu ft) cement plug 6058-5412'
2. Spotted 37 sx (43.66 cu ft) cement plug 3900-3573'.
3. Perf 4 holes @ 800' and pumped 5 sx cement through AF
4. Spotted 3 sx cement in top of 5-1/2" csg. AS

5. Installed dry hole marker

6. Filled pits and leveled location.

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs TITLE Agent

DATE 11-29-79

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITEL

DATE _____

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

~~COPY TO ALBQ.~~

*See Instructions on Reverse Side

rough perfs

**APPROVED
AS AMENDED**

JAN 10 1985

9. W. C. MILLENBACH
AREA MANAGER