1 8 F

5. LEASE

SF 079289A

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME San Juan 28-7 Unit
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas de other	San Juan 28-7 Unit
2. NAME OF OPERATOR	9. WELL NO.
El Paso Natural Gas Company	255 10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Basin Dakota
P.O. Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
 LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 	AREA Sec. 15, T-28-N, R-7-WN.M.P.M.
AT SURFACE: 1890' N, 1130' W	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Rio Arriba New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6118' GL
TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
MULTIPLE COMPLETE	change on Form 9-330.)
CHANGE ZONES	
ABANDON*	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent	rectionally drilled give subsurface locations and
6-22-78: TD 3170'. Ran 71 jts. 7", 20#, K-5. 3170'. Cemented w/272 cu. ft. cement. WOC 1	5 intermediate casing, 3158' set at 2 hours, held 1200#/30 minutes.
Top of cement at 1300'.	
6-28-78. TD 7323! Dan 196 its 4 1/2!! 10	Г С11 С4 И ГГ 1 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4
6-28-78: TD 7323'. Ran 186 jts. 4 1/2", 10. 7312' set 7323'. Float collar set at 7317'. WOC 18 hrs.	Cemented w/643 cu. ft. cement.
2-08-79: PBTD 7317'. Tested casing to 4000# 7086,7174,7178,7181,7212,7239,7245,7268' w/1 99,000# 20/40 sand and 71,000 gal. water.	OK. Perfed 7054,7057,7060,7079, SPZ. Fraced w/13.000# 10/20 sand
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	- 1
SIGNED No. F. Guseo TITLE Drilling Cler	rk date 2-28-79
(This space for Federal or State office use)	
APPROVED BY	<u></u> 스탠딩이를 걸음 성능적인 (1997)
APPROVED BYTITLE CONDITIONS OF APPROVAL, IF ANY:	DATE