UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

	and access as a subserver	<u> </u>
_	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	SUNDRY NOTICES AND REPORTS ON WELLS to not use this form for proposals to drill or to deepen or plug back to a different servoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
		San Juan 28-6 Unit
rese		8. FARM OR LEASE NAME
1	oil gas 🗔	San Juan 28-6 Unit
••	well well other	9. WELL NO.
2.	NAME OF OPERATOR	60 A
	El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME
3.	ADDRESS OF OPERATOR	Blanco MV
-	Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4.	LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA Sec. 21, T-28-N, R-6-W
	AT SURFACE: 1460'S, 970'E	12. COUNTY OR PARISH 13. STATE
	AT TOP PROD. INTERVAL:	Rio Arriba New Mexico
	AT TOTAL DEPTH:	14. API NO.
16.	CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
	REPORT, OR OTHER DATA QUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6486' G.L.
TES FRA SHO REF PUI MU CHA ABA	QUEST FOR APPROVAL TO: ST WATER SHUT-OFF ACTURE TREAT OOT OR ACIDIZE PAIR WELL LL OR ALTER CASING DILTIPLE COMPLETE ANGE ZONES ANDON* her)	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
17.	 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statingluding estimated date of starting any proposed work. If well is one of the complete of	an potential and a second
	measured and true vertical depths for all markers and zones pertine PBTD 5860'. Tested casing to 3500#, OK. Per 5438,5442,5446,5495,5500,5520,5525,5530,5570 W/1 SPZ. Fraced w/67,000# 20/40 sand, 134,00 Perfed C.H. & Men. 4956,4963,4970,5060,5065,5326,5338,5374' W/1 SPZ. Fraced w/ 47,000# Flushed w/7,000 gal. water.	rfed P.L. 5418,5422,5426,5430,5434, ,5577,5615,5737,5754,5820,5830,5844' 0 gal. water. Flushed w/7250 gal. wtr 5070,5085,5091,5097,5103,5191,5200, 20/40 sand, 94,000 gal. water.
Su	PBTD 5860'. Tested casing to 3500#, OK. Per 5438,5442,5446,5495,5500,5520,5525,5530,5570 W/1 SPZ. Fraced w/67,000# 20/40 sand, 134,00 Perfed C.H. & Men. 4956,4963,4970,5060,5065,5326,5338,5374' W/1 SPZ. Fraced w/ 47,000# Flushed w/7,000 gal. water.	rfed P.L. 5418,5422,5426,5430,5434, ,5577,5615,5737,5754,5820,5830,5844' 0 gal. water. Flushed w/7250 gal. wtr 5070,5085,5091,5097,5103,5191,5200, 20/40 sand, 94,000 gal. water.
Su	PBTD 5860'. Tested casing to 3500#, OK. Per 5438,5442,5446,5495,5500,5520,5525,5530,5570 W/1 SPZ. Fraced w/67,000# 20/40 sand, 134,00 Perfed C.H. & Men. 4956,4963,4970,5060,5065,5326,5338,5374' W/1 SPZ. Fraced w/ 47,000# Flushed w/7,000 gal. water.	rk DATE August 21, 1979
Su 18 510	PBTD 5860'. Tested casing to 3500#, OK. Per 5438,5442,5446,5495,5500,5520,5525,5530,5570 W/1 SPZ. Fraced w/67,000# 20/40 sand, 134,00 Perfed C.H. & Men. 4956,4963,4970,5060,5065,5326,5338,5374' W/1 SPZ. Fraced w/ 47,000# Flushed w/7,000 gal. water.	rk DATE August 21, 1979

A. D. HERMAN DOWN