

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

P.O. Box 289, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

1520'N, 1285'W

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

AUG 14 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-15-80: TD 3743'. Ran 87 joints 7", 20#, K-55 intermediate casing 3731' set at 3743'. Cemented w/ 311 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of Cement at 2450'.

7-17-80: TD 6021'. Ran 61 joints 4 1/2", 10.5#, K-55 casing liner 2418' set 3603-6021'. Float collar set at 6004'. Cemented w/ 421 cu. ft. cement. WOC 18 hours.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED L. A. Suarez TITLE Drilling Clerk DATE July 28, 1980

(This space for Federal or State office use)

APPROVED FOR RECORD _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY.

AUG 06 1980

FARMINGTON DISTRICT

BY Bkl

*See Instructions on Reverse Side