

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other _____

b. TYPE OF COMPLETION:

NEW WELL ☐ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other _____

2. NAME OF OPERATOR

El Paso Natural Gas

3. ADDRESS OF OPERATOR

P.O. Box 289, Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 1520' North, 820' West

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

5. LEASE DESIGNATION AND SERIAL NO.

SF 078500

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 28-7 Unit

8. FARM OR LEASE NAME

San Juan 28-7 Unit

9. WELL NO.

94 A (PM)

10. FIELD AND POOL, OR WILDCAT

S. Blanco PC & Blanco MV

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 30, T-28-N, R-7-W
NMPM

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

15. DATE SPURRED

3-31-80

16. DATE T.D. REACHED

4-8-80

17. DATE COMPL. (Ready to prod.)

8-7-80

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

6294' GL

20. TOTAL DEPTH, MD & TVD

5537'

21. PLUG, BACK T.D., MD & TVD

5523'

22. IF MULTIPLE COMPL., HOW MANY*

2

23. INTERVALS DRILLED BY

ROTARY TOOLS

0-5537

CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

2832-2947 (PC) 4406-5432 (MV)

26. TYPE ELECTRIC AND OTHER LOGS RUN

FDC, ISF-IGR, Temp. Survey

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD
9 5/8"	36#	229'	13 3/4"	224 cu. ft.
7"	20#	3177'	8 3/4"	275 cu. ft.

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)
4 1/2"	3043'	5537'	432 cu. ft.	

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
1 1/4"	2930'	3055'
2 3/8"	5443'	

2832-2843, 2852-2864, 2870-2886, 2888-2900,
2913-2918, 2928-2934, 2941-2947' W/8 SPZ.
1406, 4444, 4483, 4504, 4528, 4542, 4564, 4570, 4580,
4590, 4733, 4780, 4792, 4798, 4808, 4837, 4842, 4937,
4943, 4950, 4982, 4433, 5039, 5044, 5062, 5068, 5082,
5088, 5100, 5105, 5110, 5119, 5132, 5148, 5170, 5176,
5182, 5190, 5198, 5214, 5250, 5276, 5301, 5318, 5329,

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
2905-3006'	56,000# sd, 61,000 gal. wtr.
4406-4433'	64,500# sd, 129,000 gal. wtr.
5039-5432'	77,000# sd, 154,000 gal. wtr.

33. 5414, 5424, 5432' W/1

PRODUCTION

DATE FIRST PRODUCTION

PRODUCTION METHOD (Flowing, gas lift, pumpjack, etc.)

Flowing

WELL STATUS (Producing or shut-in)

Shut-in

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
PC 8-7-80							
MV 7-31-80	3 hrs	3/4					
FLOW, TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
PC SI 865				PC 1130			
MV SI 962	SI 865			MV 7636			

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

TEST WITNESSED BY

H. E. McAnally

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records.

SIGNED

TITLE

Drilling Clerk

DATE


August 29, 1980

*(See Instructions and Spaces for Additional Data on Reverse Side)

FARMINGTON DISTRICT

BY

SEP 5 1980



ACCEPTED FOR RECORD

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:				38. GEOLOGIC MARKERS	
SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF: CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES					
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH
					TRUE VERT. DEPTH
				Ojo Alamo	1893'
				Kirtland	2950'
				Picture Cliffs	2901'
				Mesa Verde	4400'
				Menefee	4489'
				Point Lookout	5058'