Form	3160	-5
(Nove	mber	1983)
(Form	erly	9 - 331)

11-21-85

UNITED STATES

SUBMIT IN TRIPLICATES (Other instructions on re-

Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985

——————————————————————————————————————	BUREAU OF LAND MANAGEME	SF 079250	
	RY NOTICES AND REPORTS rm for proposals to drill or to deepen or plu se "APPLICATION FOR PERMIT—" for such		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL GAS X	OTHER		7. UNIT AGREEMENT NAME San Juan 28-5 Unit
2. NAME OF OPERATOR E	l Paso Natural Gas Com	pany	8. FARM OR LEASE NAME San Juan 28-5 Unit
3. ADDRESS OF OPERATOR P	ost Office Box 4289,Far	rmington,NM 87499	9. WBLL NO. 88M
4. LOCATION OF WELL (Repo See also space 17 below. At surface	ort location clearly and in accordance with a 40'N, 815'W	ny State requirements.*	10. FIELD AND POOL, OR WILDCAT Blanco MV/Basin DK
RECEIV	ED		Sec. T. B. M. OR BLK. AND Sec. 15, T-28-N, R-5-W N.M.P.M.
14. PERMIT NO. NOV 26 198	15. ELEVATIONS (Show whether	DF, RT, GR, etc.) 567 † GL	12. COUNTY OF PARISH 13. STATE Rio Arriba NM
16. BUREAU OF LAND MANA FARMINGTON RESOURCE	Check Appropriate Box To Indicate GEMENT	1	Other Data
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL (Other)	CHANGE PLANS	(Norz Report results	unning Casing of multiple completion on Well
17. DESCRIBE PROPOSED OR CO: proposed work. If wel nent to this work.) *	PLETED OPERATIONS (Clearly state all pertine is directionally drilled, give subsurface loc	Completion or Recognition of Recognition of Recognition and give pertinent dates, nations and measured and true vertical	etion Report and Log form.) including estimated date of starting any l depths for all markers and zones perti-
11-14-85	TD 3968'. Ran 92 jts. 3968'. Cemented with gel, 2% calcium chlor followed by 100 class WOC 12 hours. Held 12	n 266 sks. Class "B' ride 1/2 cu ft Perl: s B, 2% calcium chlo	", 65/35 POZ mix, 6% ite/sk (513 cu ft), oride (118 cu ft).
11-17-85	TD 6368'. Ran 57 jts. @ 6368'. Float collar Cemented with 50 sks. Halad-9 (62 cu ft), f 2% gel, 6.25# Gilsonift). WOC 18 hours.	set @ 6274'. Top o Class "B", 50/50 1 followed by 218 clas	of Liner @ 3813'. POZ mix, 2% gel, 0.6% ss B, 50/50 POZ mix,

18. I hereby certify that the foregoing is true and correct (This space for Federal or State office use) DEC 02 1985 APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

0.4% HR-7 (118 cu ft). WOC 18 hrs.

OIL CON. DIV.

TD 8059'. Ran 44 jts. 4 1/2", 11.6#, K-55 casing liner 1799'

set @ 8059'. Float collar set at 8051'. Top of liner @ 6260'. Cmt'd w/86 sks class B, 8% gel, 0.4% HR-7 (160 cu ft), followed by 100 sks class B, 1/4# fine tuf-plug/sk,

DIST. 3

*See Instructions on Reverse Side