

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well GAS	DHC-2544	API # (assigned by OCD) 30-039-23857
2. Name of Operator BURLINGTON RESOURCES	OIL & GAS COMPANY	5. Lease Number Fee
3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700		6. State Oil&Gas Lease #
4. Location of Well, Footage, Sec., T, R, M 1190'FSL, 1745'FWL, Sec.9, T-28-N, R-5-W, NMPM, Rio Arriba County		7. Lease Name/Unit Name San Juan 28-5 Unit
		8. Well No. 89E
		9. Pool Name or Wildcat Blanco MV/Basin DK
		10. Elevation:

Type of Submission	Type of Action
☐ Notice of Intent	☐ Abandonment
☒ Subsequent Report	☒ Recompletion
☐ Final Abandonment	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☒ Other - Commingle
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut off
	☐ Conversion to Injection

13. Describe Proposed or Completed Operations

5-15-00 MIRU. ND WH. NU BOP. SDON.
5-16-00 TOO H w/247 jts 1 1/2" tbgs. TIH w/CIBP, set @ 6110'. Roll hole w/8 bbl 2% KCl wtr. PT csg & CIBP to 3000 psi/15 min, OK. TOO H. ND BOP. NU WH. RD. Rig released.
5-17-00 MIRU. TIH, ran CBL-CCL-GR @ 3520-6210', TOC @ 4080'. RD.
5-21-00 MIRU. PT 4 1/2" csg to 4000 psi, OK. Perf Point Lookout w/1 SPF @ 5756, 5763, 5770, 5782, 5800, 5808, 5815, 5829, 5837, 5850, 5861, 5873, 5881, 5891, 5900', w/2 SPF @ 5930, 5944, 5954, 5967, 5975, 5983, 6012, 6040, 6051' w/33 0.32" diameter holes total. Acidize w/1050 gal 15% HCl. Frac Point Lookout w/2095 bbl slk wtr, 100,000# & csg to 4000 psi, OK. Perf Cliff House/Menefee w/1 SPF @ 5167, 5186, 5222, 5239, 5331, 5341, 5358, 5366, 5376, 5407, 5420, 5430, 5453, 5467, 5500, 5516, 5526, 5557, 5564, 5573, 5594, 5602, 5632, 5653, 5662, 5672' w/26 0.32" diameter holes total. Acidize w/1050 gal 15% HCl. Frac Cliff House/Menefee w/2085 bbl slk wtr, 100,000# 20/40 Brady sd. TOO H. TIH w/CIBP, set @ 5130'. Load hole w/2% KCl wtr. PT CIBP & csg to 4000 psi, OK. TIH, perf Lewis w/1 SPF @ 4273, 4278, 4281, 4286, 4356, 4361, 4371, 4454, 4457, 4460, 4546, 4549, 4552, 4567, 4570, 4574, 4592, 4596, 4600, 4642, 4644, 4646, 4720, 4724, 4728, 4732, 4761, 4769, 4772, 4845, 4848, 4857, 4860, 4958, 4961, 4964, 4997, 5000, 5041, 5045, 5047, 5087, 5090, 5092' w/44 0.29" diameter holes total. Acidize w/1050 gal 10% acetic acid. Frac Lewis w/733 bbl 20# linear gel, 200,000# 20/40 Brady sd. CO after frac.

Continued on back

SIGNATURE Peggy Cole Regulatory Supervisor June 15, 2000

no
(This space for State Use)

Original Signed by STEVEN N. HAYDEN

Approved by _____ Title _____ Date _____

DEPUTY OIL & GAS INSPECTOR, DIST. JUN 23 2000

5-22/24-00 Blow well & CO.
5-25-00 Blow well & CO. SD.
6 5-00 MIRU. ND WH. NU BOP. TIH w/3 7/8" mill to 4738'. Establish circ. Circ hole clean.
6-6-00 Circ hole clean. Mill out CIBP @ 5130'. TIH, circ hole clean.
6-7-00 Circ hole clean. Mill out CIBP @ 5720'. TIH, circ hole clean.
6-8-00 Circ hole clean. Mill out CIBP @ 6110'. TIH, circ hole clean.
6 9-00 Circ hole clean. TOOH w/mill. TIH, circ hole clean.
6 10/13-00 Circ hole clean.
6-14-00 Circ hole clean. TOOH. TIH w/259 jts 2 3/8" 4.7# J-55 EUE tbg, landed @ 7975'.
ND BOP. NU WH. RD. Rig released.

Well will produce as a Mesaverde/Dakota commingle under DHC-2544.